



PRAMAC GBW10Y APERTO CON QUADRO COMANDO MANUALE

Product description:

The GBW series offers reliable and powerful machines, built for professional use in support of the power grid in case of blackouts or to serve isolated locations.

Easy to transport, install and position thanks to its compact size, this model is ideal for network emergency, construction, mobile workshops and industrial applications.

Available in open or hooded version.

YANMAR/PERKINS diesel engines

? Water cooling

? Industrial silencer

? Fork base with trolleys

? Motor fluids and charged battery

? MCP manual cabinet supplied as standard with 5 sockets.

The pictures are purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 7.47

Continuous power three phase (KW): 6.81

Maximum power three phase (KVA): 9.34

Continuous power three phase (KVA): 8.51

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO



Emissions Regulations: Stage 5

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 1116

Number cylinders: 3

Cylinders' position: In line

Oil capacity (L): 3.5

Cooling: Water

Alternator: Linz E1S13SB , with brushes

Poles: 4

Fuel tank capacity (L): 51

Consumption (L/h): 2 at 75% of the load / 2.6 at 100% of the load

Running time (h): 25.6 at 75% of the load / 19.2 at 100% of the load

Length (mm): 1600

Width (mm): 870

Height (mm): 875

Dry weight (Kg): 250

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: Compound

Engine manufacturer: Yanmar

