



# PRAMAC GBW10Y

## Generator Set Three-phase

## 7.4KW MCP Enclosure and

## manual control panel

Product price:

**7,415.61 € tax excluded**

Product description:

### PRAMAC GBW10Y THREE-PHASE DIESEL GENERATOR MCP 7.4KW

The PRAMAC GBW10Y three-phase generator delivers 7.4 kW with a diesel engine running at 1500 rpm. The PRAMAC GBW10Y generator is equipped with electric start. The alternator of the PRAMAC GBW10Y generator has brushes with a compound voltage regulator. The Yanmar diesel engine makes the GBW10Y generator highly reliable, as it has been designed and built using high-quality materials.

Thanks to its soundproof canopy, this generator is super-silenced. The PRAMAC GBW10Y three-phase generator is suitable for outdoor use on construction sites or for small professional jobs outdoors. Easy to transport and maneuver thanks to its forklitable base with wheels.

#### **Technical specifications of the PRAMAC GBW10Y MCP Three-Phase Generator:**

Maximum three-phase power: 7.47 kW

Continuous three-phase power: 6.81 kW

Fuel: Diesel

Voltage: 400 V

Frequency: 50 Hz

Engine: Yanmar 3TNV76-GPGE

Starting system: Electric

Fuel consumption: 2.6 L/h at 100% load

Length: 1645 mm

Width: 870 mm

Height: 1072 mm

Weight: 460 Kg

Compound

Sockets:



---

N.1 3P+N+T CEE 400V 32A  
N.1 3P+N+T CEE 400V 16A  
N.2 2P+T CEE 230V 16A  
N.1 230V 16A SCHUKO

The PRAMAC GBW10Y generator is a professional diesel generator developed by Pramac with the features and equipment necessary to deliver a superior-class product. With its low noise level, the PRAMAC GBW10Y generator is ideal for use in residential areas or during non-working hours.

The GBW10Y generator is equipped with a reliable diesel engine, premium-quality components, and complete instrumentation. Its canopy is tilttable for convenient access to the maintenance area.

If you are looking for a generator like the GBW10Y MCP three-phase power generator, we recommend browsing our catalog of [land-based generators](#) to find the one that best suits your needs.

#### **Product features:**

Phase: Three phase

Maximum power three phase (KW): 7.47

Continuous power three phase (KW): 6.81

Maximum power three phase (KVA): 9.34

Continuous power three phase (KVA): 8.51

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Yanmar 3TNV76-GPGE, naturally aspirated

Emissions Regulations: Stage 5

Speed governor: Mechanical

Starting system: Elettrico

Engine capacity (cm<sup>3</sup>): 1116

Number cylinders: 3

Cylinders' position: In line

Oil capacity (L): 3.5

Cooling: Water

Alternator: Linz E1S13SB , with brushes

Poles: 4

Fuel tank capacity (L): 51

Consumption (L/h): 2 at 75% of the load / 2.6 at 100% of the load

Running time (h): 25.6 at 75% of the load / 19.2 at 100% of the load

---



Acoustic power: 93 dB(A)

Acoustic pressure: 64 dB(A) at 7 m

Length (mm): 1645

Width (mm): 870

Height (mm): 1072

Dry weight (Kg): 460

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : No

Voltage regulator: Compound

Engine manufacturer: Yanmar

