



PRAMAC GBW10Y Generator Set Three-phase 7.4KW ACP Enclosed with automatic control panel

Product price:

7,537.87 € tax excluded

Product description:

PRAMAC GBW10Y GENERATOR SET THREE-PHASE ACP 7.4KW

The PRAMAC GBW10Y three-phase generator delivers 7.4 kW with a diesel engine running at 1500 rpm. The PRAMAC GBW10Y generator is equipped with electric start. The alternator of the PRAMAC GBW10Y generator features brushes with compound voltage regulator. The Yanmar diesel engine makes the GBW10Y generator highly reliable, as it has been designed and built using high-quality materials.

Thanks to its soundproof enclosure, this generator is super-silenced. The PRAMAC GBW10Y three-phase generator is suitable for outdoor use on construction sites or for small professional jobs outdoors.

Technical specifications of the PRAMAC GBW10Y ACP Three-Phase Generator:

Maximum three-phase power: 7.47 kW

Continuous three-phase power: 6.81 kW

Fuel: Diesel

Voltage: 400 V

Frequency: 50 Hz

Engine: Yanmar 3TNV80F-NGPGE STAGE V

Starting system: Electric

Fuel consumption: 2.6 L/h at 100% load

Length: 1645 mm

Width: 870 mm

Height: 1072 mm

Weight: 460 Kg

Compound



ACP Automatic Control Panel:

Integrated panel connected to the generator, with a microprocessor control module that manages all electronic control, command, and monitoring circuits. Direct switching control terminal block (ACP)

N.1 3P+N+T CEE 400V 32A

The PRAMAC GBW10Y generator is a professional diesel generator developed by Pramac with the features and equipment required to deliver a superior-class product. With its low noise level, the PRAMAC GBW10Y generator is ideal for use in residential areas or during non-working hours.

The GBW10Y generator is equipped with a reliable diesel engine, high-quality components, and complete instrumentation.

If you are looking for a generator like the GBW10Y three-phase power generator, we recommend browsing our catalog of [land-based generators](#) to find the one that best suits your needs.

Product features:

Phase: Three phase

Maximum power three phase (KW): 7.47

Continuous power three phase (KW): 6.81

Maximum power three phase (KVA): 9.34

Continuous power three phase (KVA): 8.51

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE

Emissions Regulations: Stage 5

Speed governor: Mechanical

Starting system: Elettrico

Engine capacity (cm³): 1116

Number cylinders: 3

Cylinders' position: In line

Oil capacity (L): 3.5

Cooling: Water

Alternator: Linz E1S13SB , with brushes

Poles: 4

Fuel tank capacity (L): 51

Consumption (L/h): 2 at 75% of the load / 2.6 at 100% of the load

Running time (h): 25.6 at 75% of the load / 19.2 at 100% of the load

Acoustic power: 93 dB(A)

Acoustic pressure: 64 dB(A) at 7 m

Length (mm): 1645



Width (mm): 870
Height (mm): 1072
Dry weight (Kg): 460
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : Optional
Voltage regulator: Compound
Engine manufacturer: Yanmar