



# PRAMAC GBW15P APERTO CON QUADRO COMANDO AUTOMATICO

## Product description:

The GBW series offers reliable and powerful machines, built for professional use in support of the power grid in case of blackouts or to serve isolated locations.

Easy to transport, install and position thanks to its compact size, this model is ideal for network emergency, construction, mobile workshops and industrial applications.

Available in open or hooded version.

YANMAR/PERKINS diesel engines

Water cooling

Industrial silencer

Fork base with trolleys

Motor fluids and charged battery

The images are purely indicative.

## Product features:

Phase: Three phase

Maximum power three phase (KW): 11.28

Continuous power three phase (KW): 10.18

Maximum power three phase (KVA): 14.1

Continuous power three phase (KVA): 12.72

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE

Engine: PERKINS 403D-15G, naturally aspirated



---

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 1496

Number cylinders: 3

Cylinders' position: In line

Oil capacity (L): 6

Cooling: Water

Alternator: Linz E1S13MD, with brushes

Poles: 4

Fuel tank capacity (L): 51

Consumption (L/h): 2.7 at 75% of the load / 3.6 at 100% of the load

Running time (h): 18.6 at 75% of the load / 14.2 at 100% of the load

Length (mm): 1600

Width (mm): 870

Height (mm): 950

Dry weight (Kg): 390

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: Compound

Engine manufacturer: Perkins

