



# PRAMAC GBW15P APERTO CON QUADRO COMANDO AUTOMATICO

**Product price:**

**7,164.68 € tax excluded**

**Product description:**

The GBW series offers reliable and powerful machines, built for professional use in support of the power grid in case of blackouts or to serve isolated locations.

Easy to transport, install and position thanks to its compact size, this model is ideal for network emergency, construction, mobile workshops and industrial applications.

Available in open or hooded version.

YANMAR/PERKINS diesel engines

Water cooling

Industrial silencer

Fork base with trolleys

Motor fluids and charged battery

The images are purely indicative.

**Product features:**

Phase: Three phase

Maximum power three phase (KW): 11.28

Continuous power three phase (KW): 10.18

Maximum power three phase (KVA): 14.1

Continuous power three phase (KVA): 12.72

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE



Engine: PERKINS 403D-15G, naturally aspirated  
Speed governor: Mechanical  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 1496  
Number cylinders: 3  
Cylinders' position: In line  
Oil capacity (L): 6  
Cooling: Water  
Alternator: Linz E1S13MD, with brushes  
Poles: 4  
Fuel tank capacity (L): 51  
Consumption (L/h): 2.7 at 75% of the load / 3.6 at 100% of the load  
Running time (h): 18.6 at 75% of the load / 14.2 at 100% of the load  
Length (mm): 1600  
Width (mm): 870  
Height (mm): 950  
Dry weight (Kg): 390  
Silenced: No  
Super silenced: No  
Product type: Generator  
ATS Switch device : Optional  
Voltage regulator: Compound  
Engine manufacturer: Perkins