



PRAMAC GBW15P GENSET WITH AUTOMATIC CONTROL PANEL

Product description:

The GBW series offers reliable and powerful machines, built for professional use in support of the power grid in case of blackouts or to serve isolated locations.

Easy to transport, install and position thanks to its compact size, this model is ideal for network emergency, construction, mobile workshops and industrial applications.

Available in open or hooded version.

YANMAR/PERKINS diesel engines

Water cooling

LINZ Alternators Compound adjustment

Tilting casing with gas springs

Residential muffler

Lifting hook

Fork base with trolleys

Motor fluids and charged battery

Oil extraction piping

The images are purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 11.28

Continuous power three phase (KW): 10.18

Maximum power three phase (KVA): 14.1

Continuous power three phase (KVA): 12.72

Fuel: Diesel





Frequency (Hz): 50
Voltage (V): 400
Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO
Emissions Regulations: Stationary Use
Speed governor: Mechanical
Starting system: Electric
Engine capacity (cm³): 1496
Number cylinders: 3
Cylinders' position: In line
Oil capacity (L): 6
Cooling: Water
Alternator: Linz E1S13MD, with brushes
Poles: 4
Fuel tank capacity (L): 51
Consumption (L/h): 2.7 at 75% of the load / 3.6 at 100% of the load
Running time (h): 18.6 at 75% of the load / 14.2 at 100% of the load
Acoustic power: 95 dB(A)
Acoustic pressure: 66 dB(A) at 7 m
Length (mm): 1645
Width (mm): 870
Height (mm): 1072
Dry weight (Kg): 550
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : No
Voltage regulator: Compound
Engine manufacturer: Perkins

