



PRAMAC GBW15P GENSET WITH AUTOMATIC CONTROL PANEL

Product price:

9.667,50 € tax excluded

Product description:

PRAMAC GBW15P MCP Three-phase 11.2 KW Super Silent Generator

The PRAMAC GBW15P three-phase generator with 11.2 KW power has a diesel engine running at 1500 rpm. The PRAMAC GBW15P generator is equipped with an electric start. The alternator of the PRAMAC GBW15P generator has brushes with a compound voltage regulator. The Perkins diesel engine makes the GBW15P generator highly reliable as it is built and designed using top-quality materials.

Thanks to its casing, this generator is super silent. Additionally, it is easy to transport, install, and position thanks to its compact size, making this model ideal for emergency power, construction, mobile workshops, and industrial applications. The PRAMAC GBW15P three-phase generator is suitable for outdoor use on construction sites or for small professional outdoor jobs.

Technical specifications of the PRAMAC GBW15P Three-phase generator:

- Maximum Three-phase Power: 11.28 KW
- Continuous Three-phase Power: 10.18 KW
- Fuel: Diesel
- Voltage: 400 V
- Frequency: 50 Hz
- Engine: Perkins 403D-15G
- Start: Electric
- Consumption: 3.6 Lt/h at 100% load
- Length: 1645 mm
- Width: 870 mm
- Height: 1072 mm





- Weight: 550 Kg
- Compound

Sockets:

- N.1 3P+N+T CEE 400V 32A
- N.1 3P+N+T CEE 400V 16A
- N.2 2P+T CEE 230V 16A
- N.1 230V 16A SCHUKO

The PRAMAC GBW15P power generator is a professional diesel generator developed by Pramac with the characteristics and equipment necessary to obtain a superior class product. The PRAMAC GBW15P power generator, with its low noise level, is the ideal generator for use in residential areas or during non-working hours.

The GBW15P generator is equipped with a reliable diesel engine, top-quality components, and complete instrumentation.

If you are looking for a generator like the GBW15P three-phase power generator, we recommend browsing our catalog of terrestrial generators to find the one that best suits your needs.

Images and technical data are non-binding.

Product features:

Phase: Three phase

Maximum power three phase (KW): 11.28

Continuous power three phase (KW): 10.18

Maximum power three phase (KVA): 14.1

Continuous power three phase (KVA): 12.72

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Emissions Regulations: Stationary Use

Speed governor: Mechanical





Starting system: Electric
Engine capacity (cm³): 1496
Number cylinders: 3
Cylinders' position: In line
Oil capacity (L): 6
Cooling: Water
Alternator: Linz E1S13MD, with brushes
Poles: 4
Fuel tank capacity (L): 51
Consumption (L/h): 2.7 at 75% of the load / 3.6 at 100% of the load
Running time (h): 18.6 at 75% of the load / 14.2 at 100% of the load
Acoustic power: 95 dB(A)
Acoustic pressure: 66 dB(A) at 7 m
Length (mm): 1645
Width (mm): 870
Height (mm): 1072
Dry weight (Kg): 550
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : No
Voltage regulator: Compound
Engine manufacturer: Perkins

