



Shop name



PRAMAC GBW15Y Generator Set Three-phase MCP 11.4KW Coffered with manual control panel

Product price:

8,033.31 € tax excluded

Product description:

PRAMAC GBW10P GENERATOR SET THREE-PHASE MCP 9.65KVA

The PRAMAC GBW10P single-phase/three-phase generator is equipped with a Perkins 403D-11G diesel engine, capable of delivering a power output of 9.65 KVA, complete with a Compound voltage regulator.

The PRAMAC GBW10P generator is fitted with an electric start and a manual control panel that allows you to view all electrical parameters of the engine and generator, monitor functions and operating status, manage the entire unit, and display any errors or alarms if they occur.

The PRAMAC GBW10P comes with a soundproof canopy, made of galvanized sheet metal, bent and electro-welded, with IP23 protection rating and side doors for both ordinary and extraordinary maintenance. The generator ensures efficient and quiet operation thanks to the Perkins 403D-11G diesel engine, which delivers a maximum power output of 9.65 KVA.

Technical specifications PRAMAC GBW10P MCP:

Phase type: Single-phase / Three-phase

Continuous power: 8.71 KVA / 6.97 KW

Maximum power: 9.65 KVA / 7.72 KW

Engine: Perkins 403D-11G

Engine speed: 1500 rpm

Emissions standard: Non-certified

Starting system: Electric

Fuel: Diesel

Available terminal voltage: 230 / 400 V

Frequency: 50 Hz



Voltage regulator: Compound
Tank capacity: 50 L
Fuel consumption at 75% load: 1.98 L/h
Autonomy at 75% load: 25.76 h
Noise level: 66 dB(A) @ 7 m
Length: 1645 mm
Width: 870 mm
Height: 1072 mm
Dry weight: 460 Kg

Sockets:

N.1 3P+N+T CEE 400V 32A
N.1 3P+N+T CEE 400V 16A
N.2 2P+T CEE 230V 16A
N.1 230V 16A SCHUKO

Are you looking for a generator similar to the PRAMAC GBW10P MCP but with different technical specifications? [CLICK HERE](#) to explore our dedicated section of PRAMAC generators or other specialized brands.

Product features:

Phase: Single phase / Three phase
Maximum power three phase (KW): 10.8
Continuous power three phase (KW): 10
Maximum power three phase (KVA): 13.5
Continuous power three phase (KVA): 12.6
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO
Engine: Yanmar 3TNV88-BGPGE, naturally aspirated
Emissions Regulations: Stage 5
Engine rpm (rpm): 1500
Speed governor: Mechanical
Starting system: Elettrico
Engine capacity (cm³): 1642
Number cylinders: 3
Cylinders' position: In line
Oil capacity (L): 6.9
Cooling: Water
Alternator: Linz E1S13MD, with brushes



Poles: 4

Fuel tank capacity (L): 51

Consumption (L/h): 2.8 at 75% of the load / 3.8 at 100% of the load

Running time (h): 18 at 75% of the load / 13.5 at 100% of the load

Acoustic power: 93 dB(A)

Acoustic pressure: 64 dB(A) at 7 m

Length (mm): 1645

Width (mm): 870

Height (mm): 1072

Dry weight (Kg): 430

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : No

Voltage regulator: Compound

Engine manufacturer: Yanmar