



GENSET MG 50 I-SY - SIN GLE-PHASE/THREE-PHASE GENERATOR 44 KVA AVR Stage 0

Product price:

11,715.00 € tax excluded

Product description:

GENSET MG 50 I-SY - SINGLE-PHASE-THREE-PHASE ELECTRIC GENERATOR 44 KVA AVR Stage 0

The three-phase 44 KVA diesel generator is the ideal solution for those who need a reliable and powerful energy source in professional or domestic contexts.

Main features GENSET MG 50 I-SY:

High power:

Three-phase maximum power: 44 KVA (35.2 kW)

Three-phase continuous power: 39.6 KVA (31.68 kW)

Single-phase maximum power: 14.6 KVA (11.68 kW)

Yanmar 4TNV98T engine (STAGE 0): Reliable, high-performance, liquid-cooled 4-cylinder diesel engine complying with STAGE 0 emission standards.

origino complying with office o chilosion standards.

Electric start: Quick and easy starting with key.

Efficient consumption: Low fuel consumption (8.1 Lt/h) for optimum range.

Super silent: Soundproof design for silent operation.

Robust construction: Compact and robust design for easy transport and storage



Technical specifications GENSET MG 50 I-SY

Maximum three-phase power: 44 KVA Maximum three-phase power: 35.2 KW

Three-phase continuous use power: 39.6 KVA Three-phase continuous use power: 31.68 KW

Single-phase maximum power: 14.6 KVA Maximum power single-phase: 11.68 KW

Fuel: Diesel

Voltage: 230/400 V Frequency: 50 Hz

Engine: Yanmar 4TNV98T (STAGE 0)

Starter: Electric

Consumption: 8.1 Lt/h

Tank: 40 lt

Length: 1900 mm Width: 910 mm Height: 1100 mm Weight: 735 Kg Super silenced

AVR

if you are looking for a generator set such as GENSET MG 50 I-SY or with similar characteristics? CLICK HERE.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 11.68
Maximum power single phase (KVA): 14.6
Maximum power three phase (KW): 35.2
Continuous power three phase (KW): 31.68
Maximum power three phase (KVA): 44
Continuous power three phase (KVA): 39.6

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 63A CEE - 1 x 400V 32A CEE - 1 x 230V 32A CEE - 230V 16A

CEE

Engine: Yanmar 4TNV98T, 4 stroke Emissions Regulations: Stage 0



Engine rpm (rpm): 1500 Starting system: Electric Engine capacity (cm³): 3319

Number cylinders: 4 Cooling: Water

Alternator: Synchronous Protection degree: IP23 Motor insulation class: H Fuel tank capacity (L): 40 Consumption (L/h): 8.1 Running time (h): 4.94 Acoustic power: 95 dB(A)

Acoustic pressure: 70 dB(A) at 7 m

Length (mm): 1900 Width (mm): 910 Height (mm): 1100 Dry weight (Kg): 735

Silenced: Yes

Super silenced: Yes Product type: Generator ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Yanmar