



BM2 MAX 16015 High Pressure Cleaner 160 bar

Product price:

1.481,25 € tax excluded

Product description:

BM2 MAX 16015 HIGH PRESSURE CLEANER 160 BAR

The BM2 MAX 16015 High-Pressure Washer 160 bar, with its capability of 160 bar, is meticulously crafted

to ensure top-notch performance and unwavering reliability across diverse applications. Renowned for its

sturdy build and cutting-edge technological advancements, it stands as a testament to excellence in the realm of pressure washers.

The BM2 MAX 16015 boasts piston pumps with ceramic and brass heads, ensuring durability and resistance to wear. This setup ensures consistent and reliable performance, ideal for frequent and

intensive operations. The 1450 rpm motors offer an optimal balance between power and durability,

with reduced rotation speed prolonging the motor's life and reducing operational noise, enhancing the user experience.

The high-efficiency motor of the BM2 MAX 16015 guarantees excellent energy efficiency, reducing consumption without compromising performance. Additionally, the coupling protection system

between the motor and pump (SJ) protects the coupling, preventing damage and reducing maintenance costs. The motor's thermal protection is another key feature that helps prevent

overheating and failures, ensuring a long operational life for the machine.

The BM2 MAX 16015 features a Delayed Total Stop (TSD) system, which automatically shuts off the

machine a few seconds after releasing the trigger, reducing wear on the pump and motor. The painted structure with AISI 430 stainless steel cover provides excellent corrosion protection,





making the machine suitable for challenging work environments and adverse weather conditions.

The BM2 MAX 16015 High Pressure Washer 160 bar is equipped with two 260 mm wheels that facilitate

transportation and maneuverability, even on uneven surfaces. With a maximum pressure of 160 bar

(16 MPa) and a maximum flow rate of 600 liters per hour, the BM2 MAX 16015 easily tackles the most demanding cleaning tasks. The E2 pump and TSD shutdown system, combined with the pump's rotation at 1450 rpm, ensure high performance.

The BM2 MAX 16015 High Pressure Washer 160 bar operates at a supply voltage of 230 V and a frequency of 50 Hz, with a maximum absorbed power of 2.5 kW. The maximum supply temperature

is 40°C, making it suitable for a wide range of cleaning applications. The 25035 nozzle type ensures

uniform distribution of high-pressure water, improving cleaning effectiveness.

In conclusion, the BM2 MAX 16015 High Pressure Washer 160 bar represents an excellent choice for

those seeking an efficient and durable high-pressure cleaner. With its advanced features and robust construction, it is ideal for meeting the needs of both demanding professionals and home users.

Technical Specifications BM2 MAX 16015:

Phase type: Three-phase

Frequency: 50 Hz Voltage: 400 V

Maximum pressure: 160 bar - 16 Mpa - 2300 psi

Maximum flow rate: 900 Lt./h

Pump: IP47

Stop system: TSD

Pump speed: 1450 rpm

Maximum absorbed power: 4.5 KW Supply voltage: 400 V - 3ph - 50Hz

Maximum inlet temp: 40 °C

Nozzle type: 25055 Pallet quantities: 9 pcs

Length: 668 mm. Width: 508 mm. Height: 718 mm. Weight: 72 Kg.

BM₂





Are you looking for a hydrocleaner with different features? Here you can find the full range BM2 or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Three phase Frequency (Hz): 50 Voltage (V): 400 Pump type: IP 47

Maximum output capacity (Lt/min): 900 Transportability: Wheels and handles

Length (mm): 668 Width (mm): 508 Height (mm): 718

Feed Type: 400V - 3ph - 50Hz

maximum water temperature (°C): 40

Weight (Kg): 72

Maximum input power (KW): 4.5

Pump rotation (rpm): 1450

Maximum pressure (bar-MPa-psi): 160 - 16 - 2300

Stop system: TSD Nozzle type: 25055

