



PRAMAC GBW22P 20KVA THREE-PHASE SUPERSILENT AUTOMATIC PANEL GENERATOR

Product price:

10.822,50 € tax excluded

Product description:

PRAMAC GBW22P 20KVA THREE-PHASE SUPERSILENT AUTOMATIC PANEL GENERATOR

The PRAMAC GBW22P three-phase generator is equipped with a Perkins 404A-22G1 diesel engine and is capable of delivering a maximum power of 20 KVA.

The PRAMAC GBW22P generator comes with electric, manual, or automatic starting options using a 12V battery. It features a **Deep Sea controller** that displays all electrical parameters of the engine and generator, operational functions, generator status, and allows comprehensive management of the generator. It also displays any potential system errors or alarms.

The PRAMAC GBW22P generator ensures efficient and quiet operation, powered by the Perkins 404A-22G1 engine, capable of delivering a maximum power of 20 KVA.

PREPARATION FOR AUTOMATIC START PANEL (ATS)

The generator is prepared for use with an Automatic Start Panel (ATS), which automatically starts the generator in case of a power outage. This feature ensures uninterrupted operation and data retention during power interruptions.

Standard Equipment:

- LINZ alternators with Compound regulation
- Reversible hood with gas springs
- Residential muffler



Lifting hook
Forcible base with wheels
Engine and battery fluids
Oil extraction pipe

TECHNICAL SPECIFICATIONS PRAMAC GBW22P

Phase Type: Three-Phase
Continuous Use Power: 19.78 KVA / 15.82 KW
Maximum Power: 21.82 KVA / 17.46 KW
Engine: Perkins 404A-22G1
Emissions Regulation: Stage 0
Engine Speed: 1500 rpm
Starting: Electric / Automatic
Fuel: Diesel
Voltage at Terminals: 400 V
Frequency: 50 Hz
Voltage Regulator: Compoud
Socket Panel: 1 x 400V CEE 32A | Terminal block
Tank Capacity: 51 l
Consumption at 75% Load: 3.98 l/h
Autonomy at 75% Load: 12.81 h
Sound Pressure: 66 dB(A) @ 7 m
Length: 1645 mm
Width: 870 mm
Height: 1072 mm
Dry Weight: 565 Kg

Looking for a generator with different technical specifications? Check out the dedicated section for PRAMAC generators or other specialized brands.

Images and technical data are not binding.

Product features:

Phase: Three phase
Maximum power three phase (KW): 17.46
Continuous power three phase (KW): 15.42
Maximum power three phase (KVA): 21.82
Continuous power three phase (KVA): 19.78
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 400





Sockets configuration: 1 x 400V CEE 32A | Terminal block
Engine: Perkins 404D-22G
Emissions Regulations: Stage 0
Speed governor: Mechanical
Starting system: Electric / Automatic
Engine capacity (cm³): 2216
Number cylinders: 4
Cylinders' position: In line
Oil capacity (L): 10.6
Cooling: Water
Alternator: Linz E1S13MF, with brushes
Poles: 4
Fuel tank capacity (L): 51
Consumption (L/h): 4 at 75% of the load / 5.3 at 100% of the load
Running time (h): 12.8 at 75% of the load / 9.7 at 100% of the load
Acoustic power: 95 dB(A)
Acoustic pressure: 66 dB(A) at 7 m
Length (mm): 1645
Width (mm): 870
Height (mm): 1072
Dry weight (Kg): 565
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : Optional
Voltage regulator: Compound
Engine manufacturer: Perkins

