



GYS MULTIWELD 200M SALDATRICE MIG - MAG Inverter

Product price:

864.00 € tax excluded

Product description:

GYS MULTIWELD 200M MIG - MAG Inverter WELDING MACHINE

GYS MULTIWELD 200M is a high-performance single-phase inverter welding machine designed to meet the MIG/MAG, flux-cored wire and MMA needs of hobbyists and professionals. Equipped with an intuitive interface, precise unwinding system and advanced technologies, this machine guarantees flawless welding results on a variety of materials, including aluminium.

Key features GYS MULTIWELD 200M:

GYS MULTIWELD 200M Welding processes: MIG/MAG (steel wire, stainless steel, aluminium), flux cored wire (reverse polarity), MMA (basic and rutile electrodes up to Ø 4 mm)

Manual adjustment of arc dynamics: For precise control of arc stability and welding quality.

GYS Welding aid: Table on the front panel for easy setting of tension and wire diameter according to the thickness of the material to be welded.

GYS Intuitive interface: Digital screens that can be read even in bright sunlight, buttons and knobs suitable for grooved hands for simple and convenient operation.

4-roller unrolling system: Compatible with wire coils Ø 200/300 mm, ensures smooth and even wire unrolling.

GYS MULTIWELD 200M Powerful wire feeder: Ensures constant wire feed for precise, uninterrupted welding.

GYS MULTIWELD 200M European torch connection: Quick and safe torch assembly/disassembly.



GYS Compatible electrical sockets: US (type A) and EURO (types C/E/F) for greater flexibility.

GYS MULTIWELD 200M Pre-installed socket for gas heater: For welding under pure CO2 (heater not included).

GYS MULTIWELD 200M Sturdiness and portability: Reinforced wheels for stability and manoeuvrability, holder for gas cylinders up to 4 m³ (20L).

GYS MULTIWELD 200M MIG - MAG Inverter WELDING MACHINE: The ideal choice for those looking for a versatile, high-performance and easy-to-use welding machine. Perfect for maintenance, repair and construction work in the workshop, construction site or for hobby use.

Technical specifications GYS MULTIWELD 200M:

Supply voltage: 230 V

Mains frequency: 50/60 Hz

Adjustable welding current (MIG & MAG):

230V - I2 MMA: 30 - 180A

230V - I2 MIG: 30 - 200A

Reference standards:

EN 60974-1 (40°C) for MIG

EN 60974-1 (40°C) for MAG

Weight: 34.5 Kg

Degree of protection: IP 21

Product dimensions: 770 x 790 x 470 mm

Absorbed power: 9 Kw

MACHINE THICKNESS

GAS in 230V: 0.6

NO GAS in 230V: 1.2

Electronic Control: Automatic

Looking for a portable welding machine with different features? [Here](#) you can find the whole range of GYS or other specialized brands

Images and technical data are not binding and may be subject to revision by the supplier

Product features:

Phase: Single phase

Frequency (Hz): 50 / 60

Voltage (V): 230

Protection degree: IP21



Product dimensions (mm): 770 x 790 x 470

No-load voltage (V): 65

Regulation current (A): 230V in I2 MMA: 30 - 180A / 230V in I2 MIG: 30 - 200A

Type of welding: MIG-MAG

Weight (Kg): 34.5

EN 60974-1 (40°C) 230V: MIG-MAG: IA (60%): 115 A 100%: 90A / MMA IA (60%): 104 A 100%: 80 A