





Product price:

2.691,00 € tax excluded

Product description:

FENZI G5 Cistern 4900LT

FENZI G5 Cistern 4900LT: Complete solution for the safe storage of diesel fuel

The FENZI G5 Cistern 4900LT is an above-ground cistern for diesel fuel designed to meet the needs of heating and powering generator sets. Made in compliance with Italian regulations (DM 31/07/1934, DM 28/04/2005, DM 13/07/2011 and DM 22/11/2017),

it offers a complete and safe solution for storing diesel fuel.

Fenzi materials:

FENZI G5 tank: the heart of the system, where diesel fuel is stored safely and reliably.

110% FENZI G5 containment basin: capable of retaining the entire contents of the tank in the event of a spillage, guaranteeing maximum environmental protection.

90% FENZI G5 load limiting valve: prevents overloading of the tank, preventing accidents and damage.

FENZI G5 external float level indicator: allows the level of residual diesel fuel in the tank to be easily monitored.

Manhole FENZI G5 Ø 420 mm: easy access for inspection and maintenance inside the tank.

Vacuum lifting eyebolts FENZI G5: facilitate transport and positioning of the tank.

FENZI G5 unloading sleeve for cleaning: allows the tank to be easily emptied for cleaning and maintenance.





FENZI G5 earthing and equipotential bonding socket: guarantees the electrical safety of the installation.

- 1" external suction connection with FENZI G5 non-return valve: allows quick and safe withdrawal of diesel fuel.
- 1" FENZI G5 ball valve: regulates the flow of diesel in and out of the tank.
- 1" galvanised steel pipe with FENZI G5 flexible end: connects the cistern to the diesel fuel delivery system.

Technical characteristics Fenzi Tanks:

Capacity: 4900 litres

Length: 3150 mm

Width: 1850 mm

Height: 2500 mm

Intake Inches: 1"

If you are looking for a product like FENZI G5 4900LT Cistern with different characteristics, check out HERE.

Images and data purely indicative.

Product features:

Tank capacity (L): 4900

Length (mm): 3150 Width (mm): 1850 Height (mm): 2500 withdrawal inches: 1"

