



Shop name



# CGM V150F Generating Set Three-phase with Manual Panel 165KVA STAGEV

Product price:

**43,991.00 € tax excluded**

Product description:

## CGM V150F Generating Set Three-phase with Manual Panel 165KVA STAGEV

CGM V150F Three-Phase Generator Set with Manual Panel 165KVA STAGEV is the ideal solution for those who need a powerful, reliable and silent power source. With its maximum three-phase power of 132 KW / 165 KVA and three-phase continuous power of 120 KW / 150 KVA, this generator is capable of powering a wide range of devices, from construction sites to events, from farms to homes and offices.

Powered by diesel, the CGM V150F guarantees efficient and low-consumption operation, with a consumption of 17 l/h at 50% load, 24.6 l/h at 75% load and 32.8 l/h at 100% load of load.

The super-silent design makes it ideal for use in noise-sensitive environments, while the AVR (Automatic Voltage Regulator) guarantees a constant output voltage to protect connected devices. Compliant with European exhaust emission regulations for diesel engines (Stage V), the CGM V150F is an environmentally friendly and responsible choice.

## Technical Characteristics CGM V150F Three Phase with Manual Panel 165KVA STAGEV

Phase type: Three-phase

Three-phase maximum power: 132 KW / 165 KVA

Three-phase continuous power: 120 KW / 150 KVA

Fuel: Diesel

Voltage: 400V

Frequency: 50Hz

Engine: FPT NEF N67TEVP06.00

Engine rpm: 1500 rpm

Starting: Electric



Consumption: 50-75-100% load – 17 – 24.6 – 32.8 l/h

Length: 3600 mm

Width: 1200 mm

Height: 2300 mm

Weight: 3070 kg

Supersilenced

AVR

Stage V

If you are looking for a product like the CGM then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

#### **Product features:**

Phase: Three phase

Maximum power three phase (KW): 132

Continuous power three phase (KW): 120

Maximum power three phase (KVA): 165

Continuous power three phase (KVA): 150

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: Terminal box

Engine: FPT NEF N67TEVP06.00

Emissions Regulations: Stage 5

Engine rpm (rpm): 1500

Speed governor: Electronic

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 6728

Number cylinders: 6

Cooling: Water

Alternator: Stamford-Mecc Alte-Marelli Motors Self-excited, brushless

Poles: 4

Protection degree: IP44

Fuel tank capacity (L): 43

Consumption (L/h): 32.8 lt at 100% load

Running time (h): 10.2

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 3600

Width (mm): 1200

---



Shop name

Height (mm): 2300

Silenced: Yes

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: FPT Iveco

Weight (Kg): 3070



PrestaShop