



AIRSTAR Sirocco 300 ProPack LightGlobe



Product description:

AIRSTAR SIROCCO 300 PROPACK LIGHTGLOBE

The AIRSTAR Sirocco 300 ProPack LightGlobe is a cutting-edge lighting system designed to deliver exceptional performance in a variety of environments. With its advanced technology and superior features, this product is the ideal choice for those in need of a powerful and versatile lighting solution.

Main Features

Intense Brightness: With a maximum luminous output of 22,000 lumens, the AIRSTAR Sirocco 300 ProPack LightGlobe ensures clear and powerful illumination, ideal for any scenario.

Lightweight and Portable: Weighing only 2.3 kg (5.0 lb), the system is extremely easy to transport and handle.

Its light weight does not compromise its robustness and ability to withstand harsh conditions.

Daylight Color: With a color temperature of 5,000 K, the Sirocco 300 ProPack LightGlobe offers light similar to daylight, perfect for creating a natural and comfortable working environment.

Extended Durability: The average LED life is 50,000 hours, ensuring long-term use without the need for frequent replacements.

Wind Resistance: The lighting balloon can withstand winds up to 80 km/h (50 mph), making it



suitable for outdoor use in adverse weather conditions.

Energy Efficiency: With a power consumption of 160 W and an efficiency of 138 lm/W, the AIRSTAR Sirocco 300 ProPack LightGlobe is designed to provide optimal illumination with minimal energy consumption.

Technical Specifications

Lighting Data:

Light Engine: Airstar LED Matrix with 4 x 5 500 lm

Maximum lumen: 22,000 lm

Color temperature: 5,000 K

CRI: 70

Light under the balloon (2.2 m - 7.2 ft high): 345 lx - 32 fc

Light radius: 8 m - 26 ft (5 lx), 18 m - 59 ft (0.5 lx)

Illuminated surface: 201 m² (2,163 ft²) to 1,017 m² (10,946 ft²)

Technical Data:

Wind resistance: 80 km/h - 50 mph

Power consumption: 160 W

Efficiency: 138 lm/W

Battery life: 4 hours (Full Mode), 6.5 hours (Efficient Mode), 12 hours (Eco Mode)

Recommended battery: 1.7 kWh / 52 V

Certifications: IEC-60598-1, CE, IP54

Flame-retardant material

Weight and Dimensions:

Net weight of the balloon: 2.3 kg - 5 lb

Envelope dimensions: Ø 60 cm / h 37 cm (Ø 23 in / h 15 in)

Telescopic column: Up to 2.20 m (7.2 ft)

Weight: 1.6 kg (3.5 lb)

Packaging and Accessories

The AIRSTAR Sirocco 300 ProPack LightGlobe comes in an included transport case, containing:

Complete set of the lighting balloon with 1x standard envelope with telescopic column

1x 52V battery

1x battery charger

1x quick-start guide



1x envelope repair patch kit

The transport case dimensions are 67 x 51 x 26 cm (LWH), with a gross transport weight of less than 23 kg (50 lb).

Main Variants and Options

The AIRSTAR Sirocco 300 ProPack LightGlobe offers envelope variants such as lenticular, inverted reflector, and customizable options with your logo or modifications to the top color in red.

In conclusion, the AIRSTAR Sirocco 300 ProPack LightGlobe is an innovative and versatile lighting solution

that combines high brightness, portability, and energy efficiency. With its advanced features and numerous available options, this product is ideal for a wide range of applications, always ensuring excellent performance.

Looking for a Lightglobe with different technical features? [Here](#) you can find the full range of Lightglobe AIRSTAR or other specialized brands.

Images and technical data not binding.

Product features:

Voltage (V): 52 Battery

Protection degree: IEC-60598-1, CE, IP54

Power (W): 160

Maximum height (m): 2.2

Average life of LEDs (hrs): 50000

Colour temperature (°K): 5000

Type of lamps: LED

Illuminated area (m²): 1017

Total lumens (Lm): 22000



Shop name

Weight (Kg): 23

Video: lRu515jByBc



PrestaShop