



PRAMAC GSW10Y ENCLOSURE WITH MANUAL CONTROL PANEL

Product description:

PRAMAC GSW10Y MCP Three-phase 7.7 KW Super Silent AVR Generator

The PRAMAC GSW10Y three-phase generator with 7.7 KW power runs on diesel at 1500 rpm. It features an electric start. The PRAMAC GSW10Y generator's three-phase alternator is Mecc Alte brushless with AVR voltage regulator. The Yanmar diesel engine ensures reliability with high-quality materials.

Encased for super silence, easy to transport, install, and position, it's ideal for emergencies, construction, mobile workshops, and industrial use outdoors.

Technical Specifications:

- Max Three-phase Power: 7.73 KW
- Continuous Three-phase Power: 7.04 KW
- Fuel: Diesel
- Voltage: 400 V
- Frequency: 50 Hz
- Engine: Yanmar 3TNV76-GPGE
- Start: Electric
- Consumption: 2.6 Lt/h at 100% load
- Length: 1800 mm
- Width: 850 mm
- Height: 1260 mm
- Weight: 525 Kg
- AVR

Outlets:



- N.1 3P+N+T CEE 400V 32A
- N.1 3P+N+T CEE 400V 16A
- N.2 2P+T CEE 230V 16A
- N.1 230V 16A SCHUKO

The PRAMAC GSW10Y power generator is a professional diesel generator developed by Pramac, offering solutions for various applications, from continuous to emergency use. Compliant with safety and noise emission regulations, suitable for residential and industrial use. Equipped with a reliable Yanmar diesel engine and various control panel solutions, supplements, and accessories to meet diverse customer needs.

If you're seeking a generator like the GSW10Y MCP three-phase power generator, browse our catalog for the best fit.

Images and technical data are non-binding.

Product features:

Phase: Three phase

Maximum power three phase (KW): 7.73

Continuous power three phase (KW): 7.04

Maximum power three phase (KVA): 9.66

Continuous power three phase (KVA): 8.8

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Yanmar 3TNV76-GPGE, naturally aspirated

Emissions Regulations: Stage 5

Speed governor: Mechanical

Starting system: Elettrico

Engine capacity (cm³): 1116

Number cylinders: 3

Cylinders' position: In line

Oil capacity (L): 3.5

Cooling: Water

Alternator: Mecc Alte ECP3-1L, brushless



Poles: 4

Fuel tank capacity (L): 68

Consumption (L/h): 2 at 75% of the load / 2.6 at 100% of the load

Running time (h): 34.2 at 75% of the load / 25.7 at 100% of the load

Acoustic power: 94 dB(A)

Acoustic pressure: 65 dB(A) at 7 m

Length (mm): 1800

Width (mm): 850

Height (mm): 1260

Dry weight (Kg): 525

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Yanmar

