



Shop name



PRAMAC GSW10Y HOOD WITH AUTOMATIC CONTROL PANEL

Product price:

9,545.40 € tax excluded

Product description:

PRAMAC GSW10Y ACP Three-Phase 7.7 KW Super Silent AVR Diesel Generator

PRAMAC GSW10Y three-phase 7.7 KW diesel engine generator at 1500 RPM. Equipped with electric start. The three-phase alternator of PRAMAC GSW10Y is Mecc Alte, brushless with AVR voltage regulator. The Yanmar diesel engine makes it reliable due to high-quality materials. Thanks to its casing, it's super silent, easy to transport, install, and suitable for outdoor use in construction or industrial settings.

Technical specifications:

Maximum Three-Phase Power: 7.73 KW

Continuous Three-Phase Power: 7.04 KW

Fuel: Diesel

Voltage: 400 V

Frequency: 50 Hz

Engine: Yanmar 3TNV76-GPGE

Start: Electric

Consumption: 2.6 Lt/h at 100% load

Length: 1800 mm

Width: 850 mm

Height: 1260 mm

Weight: 525 Kg

AVR

Automatic Control Panel (ACP):

Integrated panel connected to the generator with a microprocessor control module that gathers all electronic circuits for command, control, and signaling. Direct switching control terminal block (ACP)



N.1 3P+N+T 400V 32A

The PRAMAC GSW10Y generator is a professional diesel generator developed by Pramac, offering various solutions for a wide range of applications, from continuous to emergency power usage. It complies with safety and noise emission regulations and can be used both in residential and industrial settings. Equipped with a reliable Yanmar diesel engine and various control panel solutions, supplements, and accessories make it versatile to meet the most demanding customer needs.

If you're looking for a three-phase ACP generator like the GSW10Y, we recommend browsing through our catalog of ground generators to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Three phase

Maximum power three phase (KW): 7.73

Continuous power three phase (KW): 7.04

Maximum power three phase (KVA): 9.66

Continuous power three phase (KVA): 8.8

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE

Engine: Yanmar 3TNV76-GPGE, naturally aspirated

Emissions Regulations: Stage 5

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 1116

Number cylinders: 3

Cylinders' position: In line

Oil capacity (L): 3.5

Cooling: Water

Alternator: Mecc Alte ECP3-1L, brushless

Poles: 4

Fuel tank capacity (L): 68

Consumption (L/h): 2 at 75% of the load / 2.6 at 100% of the load

Running time (h): 34.2 at 75% of the load / 25.7 at 100% of the load

Acoustic power: 94 dB(A)

Acoustic pressure: 65 dB(A) at 7 m



Shop name

Length (mm): 1800
Width (mm): 850
Height (mm): 1260
Dry weight (Kg): 525
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Yanmar



PrestaShop