



# PRAMAC GSW110I APERTO CON QUADRO COMANDO AUTOMATICO

## Product description:

## Product features:

Phase: Three phase

Maximum power three phase (KW): 88.7

Continuous power three phase (KW): 80.67

Maximum power three phase (KVA): 110.87

Continuous power three phase (KVA): 100.84

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: FPT NEF45TM2A, turbo aftercooler

Emissions Regulations: Stage 2

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 4500

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 12.8

Cooling: Water

Alternator: Mecc Alte ECP34-2S/4, brushless

Poles: 4

Fuel tank capacity (L): 240

Consumption (L/h): 16.3 at 75% of the load / 22.1 at 100% of the load

Running time (h): 14.7 at 75% of the load / 10.9 at 100% of the load

Length (mm): 2200

Width (mm): 1000



Height (mm): 1743

Dry weight (Kg): 1310

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: FPT Iveco

