



VISA F105GXLVM-IM SILENCED GENSET 100 KVA STAGE V

Product price:

37,760.00 € tax excluded

Product description:

VISA F105GXLVM-IM SILENCED GENSET 100 KVA STAGE V

VISA Genset F105GXLVM-IM is a state-of-the-art three-phase genset designed to provide a reliable and silent power supply, even under the most demanding conditions. With a continuous power output of 80 kW and an FPT-IVECO F36ETVP03 engine that complies with Stage V emissions regulations, this genset is the ideal solution for a wide range of applications, in both industrial and civil applications.

Key features *VISA Genset F105GXLVM-IM:*

Powerful and reliable: The FPT-IVECO F36ETVP03 4-cylinder engine ensures high performance and a long service life.

Quiet: Thanks to the Visa silencer model, the noise level is extremely low, ensuring discrete operation.

Versatile: The 400 V output voltage and 50 Hz frequency make it compatible with most electrical appliances.

Economical: Its low consumption of 20.8 litres/hour at 75% load makes it a cost-effective solution.

Robust: The solid construction and high-quality components guarantee a long service life.

Environmentally friendly: Compliant with Stage V emissions regulations.

Why choose the *VISA Genset F105GXLVM-IM?*

Construction: Ideal for powering construction equipment and lighting.



Agriculture: Perfect for powering agricultural machinery and irrigation systems.

Events: Suitable for powering sound systems, lighting and other equipment during outdoor events.

Industry: Provides emergency or continuous power for production processes.

Socket version:

SOCKET KIT NI-01: standard version

PRESE KIT NI-05: version consisting of

a watertight box mounted on the genset that includes

1 125A +3pole+N+E EEC socket protected by circuit breaker,

1 x 63A +3pole+N+E CEE socket protected by circuit breaker +

RCCB (30mA, TYPE A), 1 x 32A CEE socket +3poles+N+E

protected by dedicated circuit breaker + RCCB (30mA TYPE A)

1 x 16A +3poles+N+E EEC socket protected by circuit breaker +

RCCB (30mA TYPE A) 1 x 16A single-phase Schuko CEE socket protected by circuit breaker

+ RCCB (30mA TYPE A). Neutral connection to earth.

By choosing the NI-05 Socket Kit version, the Standard Kit version NI-01 will not be present.

Technical characteristics *VISA Genset F105GXLVM-IM:*

Phase type: Three-phase

Three-phase continuous power: 100 KVA

Three-phase continuous power: 80 KW

Voltage: 400 V

Frequency: 50 Hz

Motor: FPT-IVECO - F36ETVP03

Engine speed: 1500 rpm

Starting: Electric

Consumption: 20.8 Lt/h at 75% load

Length: 3060 mm

Width: 1200 mm

Height: 2200 mm

Fuel tank: 360 L

Supersilenced

Number of cylinders: 4

Cooling: Water

Electronic Regulator: Standard

Stage V

Silencer Model: Visa



sound pressure: 65dBA(+/-3)@7m

If you are looking for a product such as the VISA then you can browse the entire VISA [generator](#) range or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Three phase

Continuous power three phase (KW): 80

Continuous power three phase (KVA): 100

Frequency (Hz): 50

Voltage (V): 400

Engine: FPT-IVECO - F36ETVP03

Emissions Regulations: Stage 5

Engine rpm (rpm): 1500

Starting system: Electric

Engine capacity (cm³): 3600

Number cylinders: 4

Cooling: Water

Tank capacity (L): 360

Consumption (L/h): at 75% (P.R.P.) 20.8 l/h

Acoustic pressure: 65 dB(A) at 7 m

Length (mm): 3060

Width (mm): 1200

Height (mm): 2200

Silenced: Yes

Product type: Generator

Engine manufacturer: FPT Iveco

