



# RIBIMEX Variable displacement pump Pro 7200 l/h

Product price:

**447.00 € tax excluded**

## Product description:

### RIBIMEX Variable displacement pump Pro 7200 l/h

RIBIMEX Variable displacement pump Pro 7200 l/h: Efficiency and power for every need

The RIBIMEX Pro 7200 l/h variable displacement pump is an innovative and high-performance solution for pumping water. Thanks to its advanced technology and AISI 304 stainless steel construction, this pump guarantees reliability and durability, even under heavy-duty conditions.

## Main features:

**Adjustable flow rate:** Thanks to the digital press-control, the pump automatically adapts the flow rate and pressure according to requirements, ensuring energy savings and greater efficiency.

**Self-priming:** Sucks water from a depth of up to 7 metres, making it ideal for applications such as watering gardens, filling cisterns and transferring liquids.

**Powerful and versatile:** With a maximum flow rate of 7200 l/h and a head of 45 metres, it can cope with a wide range of applications.

**Robust construction:** The AISI 304 stainless steel body and 4 stainless steel turbines guarantee corrosion resistance and a long service life.

**Easy to use:** The digital control panel is intuitive and makes it easy to set the different functions.

## Advantages:

**Energy efficiency:** Automatically adapts the flow rate according to requirements, reducing

---



consumption.

Versatility: Ideal for multiple applications, both domestic and professional.

Reliability: Built with high quality materials for long life.

Easy to use: The digital control panel is intuitive.

Quiet: Ensures quiet operation.

### **TENIC FEATURES:**

Self-priming multi-cell surface pump

Automatic adjustment of  
flow rate and pressure adjustable in the  
digital keypad.

Digital Press-Control ensuring the function  
on/off function of the pump and the  
switch off in the event of a water shortage.  
of water. Autonomous and intelligent, it calibrates  
intensity of the pump, guaranteeing energy savings.  
energy saving.

Power 1 300 W.

Electric cable 1.3 m.

4 AISI 304 stainless steel turbines included.

Max. flow rate 7 200 l/h.

Suction 0 to 120 L/mn min.

Max. immersion depth 7 m. Head: 45 m.

Inlet thread 1" ¼.

Outlet thread 1'.

Pressure: min 1,3 bar, max 4,5 bar.

2L reservoir.

Stainless steel body.

Are you looking for a motorpump with different features? [Here you can find](#) the full range of motor pumps RIBIMEX and other specialized brands.

Images and technical data are not binding.

---



**Product features:**

Power (W): 1300

Maximum use depth (m): 7

Tank capacity (L): 2

Capacity (Lt/h): 7200

Inducton system: at 0 to 120 L/mn

Maximum pressure (Bar): 4,5 bar

Pump body: Inox