



TECNOGEN AP30TL-IPA THREE-PHASE PTO GENERATOR 30KVA

Product description:

TECNOGEN AP30TL-IPA THREE-PHASE PTO GENERATOR 30KVA

TECNOGEN AP30TL-IPA THREE-PHASE PTO GENERATOR 30KVA: Power and reliability in a single product

The TECNOGEN AP30TL-IPA is a powerful 30 kVA three-phase cardan shaft-driven electric generator designed to offer exceptional performance in any working condition. Thanks to its robust construction and numerous protections, this generator is the ideal solution for powering equipment and machinery on construction sites, farms, outdoor events and wherever reliable electrical power is needed.

Key features:

High power: With an output of 30 kVA, the TECNOGEN AP30TL-IPA is capable of powering a wide range of users, even the most demanding ones.

Robustness and reliability: The IP44 and IP54 protection, impregnated winding and isolation relay guarantee safe and durable operation, even in harsh and dusty environments.

Versatility: Thanks to the function selector switch and numerous sockets, the generator can be adapted to different requirements.

Safety: Electronic protection devices against overload, overvoltage, undervoltage and overfrequency ensure maximum safety.

Ease of use: The intuitive control panel and multifunctional digital instrument make the generator easy to use.

Technical characteristics:

30 (24) kVA (kW) - cosPhi 0.8 400V 50HZ

Sockets:

1x32A 5p h6



1x16A 5p h6
1x16A 3p h6
1x63A 5p h1 spec.
Coupling category 2
Power take-off: 1",3/8 Z6
Transmission ratio: 1:3.5
No. of revolutions PTO -U/min. (50HZ): 430
Min. power PTO shaft - kW (HP): 32 (44)
Tractor Power (PS) ?: > 80
Length: 1000 mm
Width: 670 mm
Height: 1100 mm
weight: 300 Kg

If you are looking for another product then you can see on our catalog other PTO [shaft generators](#).

Images and technical data are not binding.

Product features:

Maximum power three phase (KW): 24
Maximum power three phase (KVA): 30
Sockets configuration: 1x32A 5p h6 1x16A 5p h6 1x16A 3p h6 1x63A 5p h1 spec.
Transmission ratio: 1 : 3.5
Length (mm): 1000
Width (mm): 670
Height (mm): 1100
Weight (Kg): 350
Power take-off: 1",3/8 Z6
No. of revolutions PTO -U/min. (50HZ): 430
Min. power at PTO shaft - kW (HP): 32 (44)
Tractor Power (PS) ?: greater than 80

