



# Generator set 66KVA Silent Stage II

## **Product price:**

12,933.00 € tax excluded

## **Product description:**

# Generator set 66KVA Silent Stage II

66KVA Silent Stage II Generator - Power and Reliability

This three-phase generator is the ideal solution for providing emergency or continuous power supply in various industrial and commercial applications. With a maximum power of 66 KVA and a continuous power of 60 KVA, this generator is capable of powering a wide range of electrical equipment, even under high load conditions.

#### Main features:

Powerful engine: Equipped with a robust FPT N45SM1A diesel engine, synonymous with reliability and durability.

Regulatory compliance: Complies with Stage II emissions regulations, ensuring low environmental impact.

Silence: Thanks to the soundproofing system, the noise level is reduced, allowing use in noise-sensitive environments.

Compact and easy to handle: With small dimensions (2260x1000x1420 mm) and a weight of 1250 kg, it is easy to transport and install.

Autonomy: The 100-liter tank guarantees adequate autonomy for many applications.

Protection: The IP23 protection rating ensures good resistance to dust and water splashes.

Electric start: The electric start makes starting the generator quick and easy.

## **Technical Features:**

Maximum three-phase power: 66 KVA Continuous three-phase power: 60 KVA Maximum three-phase power: 53 KW Continuous three-phase power: 48 KW

Fuel: Diesel

Voltage: 230/400 V



Engine: FPT N45SM1A Protection rating: IP23

Start: Electric

Tank capacity: 100 lt. Length: 2260 mm Width: 1000 mm Height: 1420 mm Weight: 1250 Kg

If you are looking for a product with similar characteristics **CLICK HERE**.

Images and technical data are purely indicative.

## **Product features:**

Phase: Three phase

Maximum power three phase (KW): 53 Continuous power three phase (KW): 48 Maximum power three phase (KVA): 66 Continuous power three phase (KVA): 60

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400 Engine: FPT N45SM1A

Emissions Regulations: Stage 2

Engine rpm (rpm): 1500 Speed governor: Mechanical Starting system: Electric Engine capacity (cm³): 4500

Number cylinders: 4 Cylinders' position: In line Protection degree: IP23 Fuel tank capacity (L): 100

Consumption (L/h): 13.3 at 75% Load

Running time (h): 10.2

Acoustic pressure: 65 dB(A) at 7 m

Length (mm): 2260 Width (mm): 1000 Height (mm): 1420 Dry weight (Kg): 1250

Silenced: Yes

Super silenced: Yes

ATS Switch device: Optional



Voltage regulator: AVR

