



PRAMAC GSW140I HOOD WITH MANUAL CONTROL PANEL (MCP)

Product price:

22,272.58 € tax excluded

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 140.21 Continuous power three phase (KW): 101.97 Maximum power three phase (KVA): 140.21 Continuous power three phase (KVA): 127.46

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 400

Engine: FPT NEF67SM1A, turbocharged

Speed governor: Mechanical Starting system: Electric Engine capacity (cm³): 6 Number cylinders: 6

Cylinders' position: In line Oil capacity (L): 17.2

Cooling: Water

Alternator: Mecc Alte ECP34-1L, brushless

Poles: 4

Fuel tank capacity (L): 350

Consumption (L/h): 21.5 at 75% of the load / 28.2 at 100% of the load Running time (h): 16.2 at 75% of the load / 12.4 at 100% of the load

Acoustic power: 97 dB(A)

Acoustic pressure: 68 dB(A) at 7 m

Length (mm): 3400 Width (mm): 1250



Height (mm): 1770 Dry weight (Kg): 1995 Inverter: No

AVR: Yes

Compound: No Silenced: Yes

Super silenced: Yes

