



PRAMAC GSW150P COFANATO CON QUADRO COMANDO AUTOMATICO

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 118.4 Continuous power three phase (KW): 110.27 Maximum power three phase (KVA): 148 Continuous power three phase (KVA): 137.84

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 400

Engine: PERKINS 1106A-70TG1, turbocharged

Speed governor: Mechanical Starting system: Electric Engine capacity (cm³): 7000

Number cylinders: 6

Cylinders' position: In line Oil capacity (L): 11.9

Cooling: Water

Alternator: Mecc Alte ECP34-1L, brushless

Poles: 4

Fuel tank capacity (L): 350

Consumption (L/h): 22.7 at 75% of the load / 29.9 at 100% of the load Running time (h): 15.4 at 75% of the load / 11.7 at 100% of the load

Acoustic power: 97 dB(A)

Acoustic pressure: 68 dB(A) at 7 m

Length (mm): 3000





Width (mm): 1150 Height (mm): 1760 Dry weight (Kg): 2080

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Perkins

