



CUMMINS C700D5 Generator set 565KW Silenced single/three-phase

Product price:

112,100.00 € tax excluded

Product description:

CUMMINS C700D5 Generator 565KW Single-phase/Three-phase Soundproofed

The CUMMINS C700D5 Generator 565KW is the ultimate solution for those in need of a reliable and

powerful energy source, ideal for both emergency and continuous use. This CUMMINS C700D5 without housing offers a primary power output of 512 kW (640 kVA) and a standby power of 565 kW (706 kVA), making it particularly suitable for critical operational contexts.

With an operating frequency of 50 Hz, the CUMMINS C700D5 Generator 565KW is diesel-powered and equipped with a robust Cummins VTA28-G5 12-cylinder engine, with turbocharging and aftercooling system. This high-quality engine reaches a nominal speed of 1500 rpm, optimizing fuel consumption efficiency and maintaining consistent performance, with a consumption rate of approximately 122 L/h at 100% load.

Compliant with stationary use regulations, the CUMMINS C700D5 Generator 565KW is the ideal choice for fixed installations, such as data centers or other essential infrastructure. The advanced cooling system ensures optimal operation even in challenging environmental conditions, supporting temperatures up to 47°C. Additionally, the electronic speed regulator ensures stable and safe power output, preventing undesirable fluctuations.

The compact structure of the CUMMINS C700D5 Generator 565KW, with dimensions of 4047mm in length, 1608mm in width, and 1942mm in height, and a dry weight of 5630 kg, facilitates installation in limited spaces without compromising power and reliability.

In summary, the CUMMINS C700D5 Generator 565KW is an excellent investment for those who require a high-performance generator, with low fuel consumption, reduced maintenance, and state-of-the-art technology, ensuring efficiency and durability over time. This solution is



perfect for applications that require continuous and reliable power supply.

Technical Features CUMMINS C700D5:

Phase type: Single-phase / Three-phase Maximum three-phase power (KW): 565 Continuous three-phase power (KW): 454 Maximum three-phase power (KVA): 706 Continuous three-phase power (KVA): 568

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400

Engine: CUMMINS VTA28G5 Engine speed (rpm): 1500 Speed regulator: Electronic Starting system: Electric Number of cylinders: 12

Number of poles: 4

Fuel consumption (L/h): 122 at 100% load

Length (mm): 4047 Width (mm): 1608 Height (mm): 1942 Dry weight (Kg): 5630 Soundproofed: Yes

Super soundproofed: Yes

Emissions regulation: Stationary Use

Looking for a generator with different technical features? <u>CLICK HERE</u> to explore the full range of CUMMINS generators and other specialized brands.

Images and technical data are not binding

Product features:

Phase: Single phase / Three phase Maximum power three phase (KW): 565 Continuous power three phase (KW): 454 Maximum power three phase (KVA): 706 Continuous power three phase (KVA): 568

Fuel: Diesel

Frequency (Hz): 50



Voltage (V): 230 / 400

Engine: CUMMINS VTA28G5

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500 Starting system: Electric Number cylinders: 12

Consumption (L/h): 122 at 100% load

Length (mm): 4047 Width (mm): 1608 Height (mm): 1942 Dry weight (Kg): 5630

Silenced: Yes

Super silenced: Yes

Compression ratio: 13.1:1 Product type: Generator

Engine manufacturer: Cummins

Inducton system: Turbocharged/ Aftercooled BMEP at set rated load, kPa (psi): 1751 (254)

Piston speed, m/s (ft/min): 7,6 (1500) Lube oil capacity, L (US gal): 83 (21,9)

Overspeed limit, rpm: 1800 ±50