



PRAMAC GSW15P COFANATO CON QUADRO COMANDO MANUALE

Product price:

7.816,00 € tax excluded

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 11.45

Continuous power three phase (KW): 10.33

Maximum power three phase (KVA): 14.31

Continuous power three phase (KVA): 12.91

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: PERKINS 403D-15G, naturally aspirated

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 1496

Number cylinders: 3

Cylinders' position: In line

Oil capacity (L): 6

Cooling: Water

Alternator: Mecc Alte ECP3-2L, brushless

Poles: 4

Fuel tank capacity (L): 68

Consumption (L/h): 2.7 at 75% of the load / 3.6 at 100% of the load

Running time (h): 24.8 at 75% of the load / 18.9 at 100% of the load

Acoustic power: 87 dB(A)
Acoustic pressure: 58 dB(A) at 7 m
Length (mm): 1800
Width (mm): 850
Height (mm): 1260
Dry weight (Kg): 745
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : No
Voltage regulator: AVR
Engine manufacturer: Perkins