



Shop name



# PRAMAC GSW15P ENCLOSURE WITH MANUAL CONTROL PANEL

Product price:

**10,040.84 € tax excluded**

## Product description:

### **PRAMAC GSW15P MCP Three-Phase 11.4 KW Super-Silent AVR Generator**

The PRAMAC GSW15P three-phase generator has an 11.4 KW output and is powered by a diesel engine running at 1500 RPM. It features an electric start and a Mecc Alte brushless alternator with an AVR voltage regulator. The Perkins diesel engine ensures high reliability due to its construction with top-quality materials and a base designed for easy transportation with carts.

Thanks to its enclosure, this generator is super-silent. Additionally, its compact size makes it easy to transport, install, and position, making it ideal for emergency backup, construction, mobile workshops, and industrial applications. The PRAMAC GSW15P three-phase generator is suitable for outdoor use on construction sites or for small professional outdoor jobs.

## **Technical Specifications of the PRAMAC GSW15P MCP Three-Phase Generator:**

- Maximum Three-Phase Power: 11.45 KW
- Continuous Three-Phase Power: 10.33 KW
- Fuel: Diesel
- Voltage: 400 V
- Frequency: 50 Hz
- Engine: Perkins 403D-15G
- Start: Electric
- Consumption: 3.6 L/h at 100% load
- Length: 1800 mm
- Width: 850 mm
- Height: 1260 mm
- Weight: 745 Kg



- AVR

**Sockets:**

- No.1 3P+N+T CEE 400V 32A

- No.1 3P+N+T CEE 400V 16A

- No.2 2P+T CEE 230V 16A

- No.1 230V 16A SCHUKO

The PRAMAC GSW15P power generator is a professional diesel generator developed by Pramac, offering many solutions for a variety of applications, from continuous use to emergency backup. The PRAMAC GSW15P power generator complies with safety and noise emission standards and can be used in both residential and industrial environments. The GSW15P generator is equipped with a reliable Perkins diesel engine, and various control panel options, accessories, and extras make it versatile and capable of meeting the most demanding customer needs.

If you are looking for a generator like the GSW15P MCP three-phase generator, we recommend browsing our catalog of terrestrial generators to find the one that best suits your needs.

Images and technical data are not binding.

**Product features:**

Phase: Three phase

Maximum power three phase (KW): 11.45

Continuous power three phase (KW): 10.33

Maximum power three phase (KVA): 14.31

Continuous power three phase (KVA): 12.91

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: PERKINS 403D-15G, naturally aspirated

Speed governor: Mechanical

Starting system: Electric

---



Engine capacity (cm<sup>3</sup>): 1496  
Number cylinders: 3  
Cylinders' position: In line  
Oil capacity (L): 6  
Cooling: Water  
Alternator: Mecc Alte ECP3-2L, brushless  
Poles: 4  
Fuel tank capacity (L): 68  
Consumption (L/h): 2.7 at 75% of the load / 3.6 at 100% of the load  
Running time (h): 24.8 at 75% of the load / 18.9 at 100% of the load  
Acoustic power: 87 dB(A)  
Acoustic pressure: 58 dB(A) at 7 m  
Length (mm): 1800  
Width (mm): 850  
Height (mm): 1260  
Dry weight (Kg): 745  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : No  
Voltage regulator: AVR  
Engine manufacturer: Perkins