



MOSA GE 7000 BBM-L Generator set 6,7 KWA AVR STAGE V

Product price:

1,463.00 € tax excluded

Product description:

MOSA GE 7000 BBM-L Generator set 6,7 KWA AVR STAGE V

MOSA GE 7000 BBM-L: Your energy always at hand

Always key everywhere MOSA GE 7000 BBM-L Generator Set 6.7 KVA is your ideal companion to tackle any situation. With a 420 cm³ Briggs&Stratton XR2100 engine, this single-phase generator can deliver a maximum power output of 6.7 KVA, ensuring reliable and continuous operation.

Perfect for every need

Customizable power: Choose between a maximum power output of 6.7 KVA and a continuous-use output of 6 KVA, tailoring the generator to your specific needs.

Compact and lightweight: At 91 kg, the MOSA GE 7000 BBM-L is easy to transport and place wherever you need it.

Quiet: With its low noise level (99 dB(A) at 1 meter and 74 dB(A) at 7 meters), you can use it without disturbing others.

Durable and Reliable: Designed for durability, the MOSA GE 7000 BBM-L is built with high-quality materials and meets Stage 5 emission regulations.

Easy to use: The pull start and mechanical voltage regulator make operating the generator simple and intuitive.

Technical Specifications MOSA GE7000 BBM-L:



Phase Type Single Phase

Maximum single-phase power (KW) 6

Single-phase continuous use power (KW) 5.4

Maximum single-phase power (KVA) 6.7

Single phase continuous use power (KVA) 6

Fuel Gasoline

Frequency (Hz) 50

Voltage (V) 230

Engine Briggs&Stratton XR2100, 4-stroke, OHV

Engine RPM (rpm) 3000

RPM regulator Mechanical

Recoil ignition

Recoil start

Displacement (cm³) 420

Number of cylinders 1

Oil capacity (L) 1.1

Cooling Air

Alternator SYNCHRONOUS, SINGLE-PHASE, SELF-CONTROLLED

Bore per stroke (mm) 90 x 66

Emissions Standards Stage 5

Weight (kg) 91

Sound power 99 dB(A) (74 dB(A) @ 7m)

Protection class G2



Product dimensions (mm) 770 x 630 x 520

If you are looking for another product like the MOSA GE7000 BBM generator set then you can browse our catalog for more <u>terrestrial generator sets</u>.

Images and technical data are not binding.

Product features:

Phase: Single phase

Maximum power single phase (KW): 6 Continuous power single phase (KW): 5.4 Maximum power single phase (KVA): 6.7 Continuous power single phase (KVA): 6

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230

Engine: Briggs&Stratton XR2100, 4 stroke, OHV

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000 Speed governor: Mechanical

Ignition: Recoil

Starting system: Pull starter Engine capacity (cm³): 420

Number cylinders: 1 Oil capacity (L): 1.1

Cooling: Air

Alternator: SINCRONO, MONOFASE, AUTOECCITATO, AUTOREGOLATO

Bore x stroke (mm): 90 x 66

Tank capacity (L): 20

Product dimensions (mm): 770 x 630 x 520

Running time (h): 7.5

Acoustic power: 99 dB(A) (74 dB(A) @ 7m)

Weight (Kg): 91

classe di protezione: G2

