



PRAMAC GSW165P COFANATO CON QUADRO COMANDO MANUALE

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 131.2

Continuous power three phase (KW): 122.1

Maximum power three phase (KVA): 164

Continuous power three phase (KVA): 152.62

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: PERKINS 1106A-70TAG2, turbocharged

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 7000

Number cylinders: 6

Cylinders' position: In line

Oil capacity (L): 11.9

Cooling: Water

Alternator: Mecc Alte ECP34-2L, brushless

Poles: 4

Fuel tank capacity (L): 350

Consumption (L/h): 24.5 at 75% of the load / 32.9 at 100% of the load

Running time (h): 14.3 at 75% of the load / 10.6 at 100% of the load

Acoustic power: 97 dB(A)

Acoustic pressure: 68 dB(A) at 7 m

Length (mm): 3000



Width (mm): 1150

Height (mm): 1760

Dry weight (Kg): 2038

Silenced: Yes

Super silenced: Yes

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Perkins

