



# MOSA GC5360HBM

## Generator with Integrated Compressor 4.6KW 230V 9.5 bar

Product price:

**5.594,00 € tax excluded**

### Product description:

MOSA GC5360 HBM Generator with Integrated Compressor 4.6KW 230V 9.5 bar

The **MOSA GC5360 HBM Generator with Integrated Compressor 4.6KW 230V 9.5bar** is a powerful and versatile solution for those who need both electrical power and compressed air in a single machine. This single-phase generator, powered by gasoline, delivers a power of 4.6KW at 230V and 50Hz, ideal for powering electrical tools and equipment in various contexts, from construction sites to maintenance activities.

The heart of the **MOSA GC5360 HBM** is the Honda GX270 engine, a 270cm<sup>3</sup> single-cylinder air-cooled engine, which ensures reliability and high performance. The starting is both manual and electric, offering flexibility in different situations. With a fuel tank capacity of 5.3 liters, the generator ensures adequate autonomy for work needs.

A distinctive feature of this model is the integrated compressor with a 10-liter aluminum tank. The compressor provides a maximum pressure of 9.5 bar and a suction capacity of 360 l/min, making it suitable for using pneumatic tools such as nailers, screwdrivers, and spray guns. The safety valve is calibrated at 11 bar, ensuring safety during use.

The **MOSA GC5360 HBM Generator with Integrated Compressor 4.6KW 230V 9.5bar** is designed to be robust and durable, with an IP44 protection rating. The product dimensions are 980 x 610 x 685 mm and the dry weight is 158 kg, facilitating transport and positioning. The noise level at 7 meters is 95 LWA (71 dB(A)), a contained value for a generator of this power.

**Technical Features** MOSA GC5360 HBM Generator with Integrated Compressor:

Phase type: Single phase





Single-phase power (KW): 4.6

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Engine: Honda GX270

Engine speed (rpm): 3000

Start: Manual / Electric

Displacement (cm<sup>3</sup>): 270

Number of cylinders: 1

Cooling: Air

Fuel tank capacity (L): 5.3

Dry weight (Kg): 158

Compressor tank capacity: 10lt (Aluminum)

Product dimensions (mm): 980 x 610 x 685

Protection degree: IP44

Noise level at 7 mt: 95 LWA (71 dB(A) – 7 m)

Available power: 4.4 KVA / 3.9 KWP

Max pressure (bar): 9.5

Safety valve calibration pressure: 11 bar

Suction capacity: 360 l/min

Looking for a generator with different technical features? [HERE](#) you can find the area dedicated to MOSA generators or other specialized brands.

Images and technical data are not binding.





**Product features:**

Phase: Single phase

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Engine: HONDA GX270

Engine rpm (rpm): 3000

Starting system: Manual / Electric

Engine capacity (cm<sup>3</sup>): 270

Number cylinders: 1

Cooling: Air

Single-phase power (KW): 4.6

Protection degree: IP44

Product dimensions (mm): 980 x 610 x 685

Fuel tank capacity (L): 5.3

Consumption (L/h): 1.8 l/h at 75% load

Dry weight (Kg): 158

Noise level at 7 m: 95 LWA (71 dB(A) – 7 m)

Tank capacity Compressor: 10lt (Aluminum)

Withdrawable Power: 4,4 KVA / 3,9 KW

Max pressure (bar): 9.5

Pressure setting safety valve: 11 bar

Suction flow rate: 360 l/min

