



# MOSA GC7360HBM Generator with Integrated Compressor 6.4KW 230V 9.5 bar

Product price:

**5.888,00 € tax excluded**

## Product description:

MOSA GC7360HBM Generator with Integrated Compressor 6.4KW 230V 9.5 bar

The MOSA **Generator with Integrated Compressor GC7360HBM 6.4KW 230V 9.5 bar** is a powerful and reliable solution for those who need both electricity and compressed air in a single machine. This single-phase generator, powered by gasoline, delivers 6.4KW at 230V and 50Hz, making it ideal for professional applications in construction sites, mobile workshops, and maintenance activities.

The heart of the **MOSA GC7360HBM** is the Honda GX390 engine, a robust and reliable single-cylinder engine with a displacement of 390/440 cm<sup>3</sup>, air-cooled, which ensures high and lasting performance. The starting system is both manual and electric, offering flexibility in various operating situations. With a fuel tank capacity of 6.1 liters, the MOSA generator ensures extended autonomy, with a consumption of 2.5 l/h at 75% load.

A distinctive feature of this model is the integrated compressor with a 10-liter aluminum tank. The compressor provides a maximum pressure of 9.5 bar and an intake flow of 360 l/min.

## Technical Features MOSA GC7360HBM:

Phase type: Single-phase  
Single-phase power (KW): 6.4  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Engine: Honda GX390  
Engine speed (rpm): 3000  
Starting: Manual / Electric





Displacement (cm<sup>3</sup>): 390 / 440  
Number of cylinders: 1  
Cooling: Air  
Fuel tank capacity (L): 6.1  
Dry weight (Kg): 170  
Compressor tank capacity: 10L (Aluminum)  
Product dimensions (mm): 980 x 610 x 685  
Protection degree: IP44  
Noise level at 7m: 95 LWA (71 dB(A) – 7 m)  
Power available: 6.5 KVA / 5.8 KWP  
Maximum pressure (bar): 9.5  
Pressure setting of safety valve: 11 bar  
Intake flow: 360 l/min  
Consumption (L/h): 2.5 l/h at 75% load

Looking for a generator with different technical features? [HERE](#) you can find the area dedicated to MOSA generators or other specialized brands.

Images and technical data are not binding.

**Product features:**

Phase: Single phase  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Engine: Honda GX390  
Engine rpm (rpm): 3000  
Starting system: Manual / Electric  
Engine capacity (cm<sup>3</sup>): 390 / 440  
Number cylinders: 1  
Cooling: Air  
Single-phase power (KW): 6.4  
Protection degree: IP44  
Product dimensions (mm): 980 x 610 x 685  
Fuel tank capacity (L): 6.1  
Consumption (L/h): 2.5 l/h at 75% load  
Dry weight (Kg): 170  
Noise level at 7 m: 95 LWA (71 dB(A) – 7 m)  
Tank capacity Compressor: 10lt (Aluminum)  
Withdrawable Power: 6,5 KVA / 5,8 KW  
Max pressure (bar): 9.5  
Pressure setting safety valve: 11 bar





Shop name

Suction flow rate: 360 l/min



PrestaShop