



PRAMAC GSW170I COFANATO CON QUADRO COMANDO AUTOMATICO

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 131.2

Continuous power three phase (KW): 126.4

Maximum power three phase (KVA): 164

Continuous power three phase (KVA): 158

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: FPT NEF67TM3A, turbo aftercooler

Emissions Regulations: Stage 2

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 6

Number cylinders: 6

Cylinders' position: In line

Oil capacity (L): 17.2

Cooling: Water

Alternator: Mecc Alte ECP34-2L, brushless

Poles: 4

Fuel tank capacity (L): 240

Consumption (L/h): 27.1 at 75% of the load / 35.6 at 100% of the load

Running time (h): 8.9 at 75% of the load / 6.7 at 100% of the load

Acoustic power: 96 dB(A)

Acoustic pressure: 67 dB(A) at 7 m





Length (mm): 3400

Width (mm): 1250

Height (mm): 1770

Dry weight (Kg): 2057

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: FPT Iveco

