



GENERAC GLT4-A K2 LIGHT TOWER 4x320W LED STAGEV



Product price:

10,708.00 € tax excluded

Product description:

GENERAC GLT4-A K2 LIGHT TOWER 4x320W LED STAGEV

GENERAC GLT4-A K2 LIGHT TOWER 4x320W LED STAGEV is an advanced mobile lighting solution, designed to offer high performance and reliability in various applications, from construction sites to outdoor events.

Key Features:

Powerful and Efficient Lighting:

Equipped with 4 x 320W LED projectors (G5 model), it guarantees a luminous flux of 211,200 Lm and an illuminated area of 9,200 m² (1 lux min).



LEDs offer a long lifespan, with over 50,000 hours of operation.

Robust and Accessible Design:

Compact dimensions to facilitate transport and storage (minimum dimensions: 2156 x 1400 x 2403 mm, maximum: 3096 x 2166 x 8334 mm).

"Gull-wing" doors for easy access to internal components.

Simplified control panel with DSE L401-MKII digital controller.

Efficiency and Sustainability:

Kubota Z482 2-cylinder, liquid-cooled engine, to reduce fuel consumption and CO2 emissions.

Large fuel tank (200/180 liters) for 257 hours of autonomy.

Liquid containment (110%) to prevent leaks.

Mobility and Robustness:

Road trailer with folding drawbar for easy transport.

Wind resistance up to 110 km/h.

Hydraulic mast lifting system and 340° rotation.

Dry weight of 923 kg.

Additional Features:

Output socket (16A) and input plug (16A).

Standard timer and optional darkness sensor.

Average sound pressure of 60 dB(A) @ 7m.



Alternator (50/60 Hz): 3.5kVA 230V / 4.2kV 240V.

Technical Specifications GENERAC GLT4-A K2 LIGHT TOWER 4x320W LED STAGEV:

Minimum dimensions (Length x Width x Height): 2156 x 1400 x 2403 mm

Maximum dimensions (Length x Width x Height): 3096 x 2166 x 8334 mm

Dry weight: 923 kg

Mast lifting system: Hydraulic

Are you looking for a lighting tower with different technical characteristics? [HERE](#) you can find the entire range of GENERAC lighting towers or other specialized brands.

Non-binding images and technical data.

Product features:

Engine: Kubota Z482

Emissions Regulations: STAGE V

Engine rpm (rpm): 1500/1800

Number cylinders: 2

Cooling: Liquid

Alternator: 3,5kVA 230V / 4,2kV 240V

Tank capacity (L): (gross/net) 200/180l

Type of lamps: LED

Illuminated area (m²): 9200

Total lumens (Lm): 211200 Lm

Mast rotation: 340°

Stability to wind (Km/h): 110km/h

Running time (h): 257 h

Acoustic pressure: 60 dB(A) @ 7m

Dry weight (Kg): 923

Type of lifting: Idraulico

Output socket: 1 (16A)

Dimensioni max. (mm): 3096 x 2166 x 8334

minimum dimensions mm: 2156 x 1400 x 2403

Liquid containment: (110%): yes

Output socket : 1 (16A)

