



Hyundai Generator Inverter 3 ,0KW Stage5

Product price:

391,00 € tax excluded

Product description:

Hyundai Inverter Generator 3.0KW Stage5

The Hyundai Inverter Generator 3.0KW Stage5 is a portable generator designed to provide reliable, high-quality electricity. This model features a 223cc displacement and offers a maximum power output of 3.0 kW with a nominal power output of 2.8 kW. It features a recoil starter, making it easy to start in a variety of situations.

The Hyundai Inverter Generator 3.0KW Stage5 is capable of supplying a voltage/frequency of 230V / 50Hz and is equipped with 2 x 16A sockets for connecting electrical devices. The engine type is a 4-stroke single-cylinder with a power of 8.0 HP. The oil capacity is 0.6 L and the fuel capacity is 15 L, allowing for prolonged operation.

Among the main features, the Hyundai Inverter Generator 3.0KW Stage5 offers:

Stabilized sine wave to safely power sensitive electronic equipment.

A 100% copper alternator for greater efficiency and durability.

A multifunction digital display to easily monitor operating parameters.

Low oil alarm to protect the engine from damage.

Output thermal protection for added safety.

Up to 30% fuel savings for economical operation.



Parallel connection socket to increase power by combining two generators.

Technical features:

Displacement: 223 cc

Maximum power: 3.0 kW

Rated power: 2.8 kW

Starting: Pull

Voltage/Frequency: 230V / 50Hz

Sockets: 2 x 16A

Engine type: Single cylinder 4-stroke

Power: 8.0 HP

Oil capacity: 0.6 L

Fuel capacity: 15 L

Dimensions: 515 x 440 x 525 mm

Net/gross weight: 27 / 32 Kg

If you are looking for a product with similar characteristics [CLICK HERE](#).

Images and technical data are not binding. Please always consult the technical data sheet released by the manufacturer. Manel Service does not assume responsibility for any changes made by the manufacturer or any typing errors.

Product features:

Phase: Single phase

Maximum power single phase (KW): 3.5

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230





Sockets configuration: 2X16A
Emissions Regulations: Stage 5
Starting system: Manual recoil
Engine capacity (cm³): 223
Product dimensions (mm): 515 x 440 x 525 mm
Weight (Kg): 27
Nominal Power Kw: 2.8