



Ecoflow Portable Battery 4KW Remote Control

Product price:

2,660.00 € tax excluded

Product description:

Ecoflow PORTABLE BATTERY 4KW REMOTE CONTROL

Ecoflow Portable Battery 4KW Remote Control, ideal for those looking for a high-performance Ecoflow Portable Battery 4KW Remote Control option.

With a capacity of 4,096 Wh and a continuous power of 4,000 W (with peaks of up to 8,000 W), this Ecoflow portable battery is perfect for professional applications, events, camping or emergency situations.

Thanks to LFP technology and a life cycle of 4,000 cycles at 80%, it guarantees long life and safety. Supports Ecoflow Portable Battery 4KW Remote Control with Wi-Fi, Bluetooth and app control, making energy monitoring and management extremely simple.

Equipped with 5 AC outputs, 100W USB-C ports, 18W USB-A, and DC outputs including Anderson port and DC5521, it is perfect for powering all types of devices. The multi-charging input reaches up to 7,000 W, compatible with the grid, solar panels and vehicle charging.

Its compact size (693 \times 341 \times 410 mm) and weight of 51.5 kg make it easily transportable, ideal for those looking for Ecoflow Portable Battery 4KW Remote Control both indoors and outdoors.

The charging system can be expanded with additional batteries, generators and even with the Smart Home Panel. You can control your Ecoflow portable battery 4kw via remote control or with your phone with the app. You can download the app for both <u>Android</u> and <u>iOS</u>, easy to install, has a guide on correct use.

Technical Features Ecoflow Portable Battery 4KW Remote Control:

INPUTS

AC charging voltage: 220-240 Vac



AC charging power: 2900 W

Solar input: 2600W, 2 ports: High PV: 30-150V/15A, 1600W max. - Low PV: 11-60V/20A,

1,000W max

Car charger input: 12V 8A max. - 48 V 20 A max

OUTPUTS

n°2 USB-A: 18 W max n°2 USB-C: 100 W max

n°1 DC5521 outputs: 5 A max n°1 Anderson output: 30 A max

GENERAL INFORMATION

Solar charge input power: 2600 W

Capacity: 4000 Wh

Cell type: LFP

Life cycle: 4000 cycles

Width: 693 mm Length: 341 mm Height: 410 mm Weight: 51.1 kg

Are you looking for an Ecoflow portable battery 4Kw with different technical characteristics? <u>HERE</u> you can find the area dedicated to Portable Batteries and UPS of specialized brands.

Images and technical data are not binding. Please always consult the technical data sheet released by the manufacturer. Manel Service does not assume responsibility for any changes made by the manufacturer or any typing errors.

Product features:

Phase: Single phase

Maximum power single phase (KW): 8 Continuous power single phase (KW): 4

Battery capacity (Wh): 4096

Length (mm): 693 Width (mm): 341 Height (mm): 410 Weight (Kg): 51.5

Inputs: Potenza di carica AC: 2900 W / Ingresso solare: 2600 W, 2 porte: FV alto: 30-150 V/15 A, 1.600 W max. FV basso: 11-60 V/20 A, 1.000 W max. / Ingresso caricabatterie auto: 12 V 8 A



max. 48 V 20 A max.

Outputs: AC output: 5 outputs, 4,000 W max / Output port DC 12.6 V/30 A, 378 W total DC5521 \times 1, 5 A max. Anderson port \times 1, 30 A max / USB-C output 2 \times USB-C, 5/9/12/15/20 V, 5 A, 100 W

max

Life span: 4.000 cycles at 80% capacity

Chemistry of the battery: LFP

