



# GENMAC APOLLO G500SS Generator Set 500KVA AVR

Product price:

**52,334.00 € tax excluded**

## Product description:

### GENMAC APOLLO G500SS Generator Set 500KVA AVR

The GENMAC APOLLO G500SS Generator Set 500KVA AVR is a high performance three-phase generator designed for professional applications requiring continuous power and reliability. Equipped with a SCANIA DC13 072A 02 14 engine at 1500 rpm and water cooling, this diesel generator set provides a continuous PRP power of 500 kVA (400 kW) and a stand-by LTP power of 550 kVA (440 kW), ensuring operational continuity even in high load situations.

It operates at 50 Hz frequency with 400/230 V voltage and features an AVR voltage regulator for a stable and safe electricity supply. The 800-litre tank allows for approximately 11.5 hours of autonomy at 75% load, making it ideal for prolonged use without interruptions.

The compact and robust structure measures 4810 mm in length, 1600 mm in width and 2460 mm in height, with a dry weight of 5000 kg. Despite the power, the noise level is contained at 77 dB(A) at 7 meters, thanks to the silenced, although not super silenced, canopy.

The GENMAC APOLLO G500SS 500KVA AVR Generator Set is the ideal choice for construction sites, industrial plants, events and all situations that require reliable, continuous and electronically controlled energy.

## Technical characteristics:

Continuous power (PRP): 500 kVA / 400 kW

Stand-by power (LTP): 550 kVA / 440 kW

Frequency: 50 Hz



Voltage: 400/230 V  
Power factor: 0.8  
PRP/LTP nominal current: 723 A / 795 A  
Engine speed: 1500 RPM  
Displacement: 12.7 litres  
Number of cylinders: 6 in line  
Aspiration: Turbo intercooler  
Cooling: Liquid  
Speed ??regulation: Electronic  
Oil capacity: 36 L  
Coolant capacity: 38 L  
Fuel consumption 100% load: 101.3 L/h  
Autonomy at 75% load: ? 11 hours  
Excitation type: Self-excited  
Regulation: AVR ( $\pm 1\%$ )  
Fuel tank capacity: 800 L  
Leakage collection tray: Yes  
S235 JR steel chassis with anti-vibration mounts  
Modular silenced bonnet with 40 mm sound-absorbing panels  
Super-silenced integrated residential muffler  
IP65 turret electrical panel with circuit breaker and remote control  
Length: 4810 mm  
Width: 1600 mm  
Height: 2460 mm  
Net weight: 5000 kg  
Sound pressure at 7 m: 77 dBA  
Engine: Scania -DC13 072A 02 14  
Emissions Regulation: Not Emitted

#### Electrical panel features

QT2A-AMF25

Self-supporting metal IP65 turret

Magneto-thermal switch

ComAp AMF25 automatic control unit

- Voltmeter, Frequency meter, Ammeter
  - Generator power reading (kW, kV Ar, kV A & pf)
  - Hour meter
-



- Fuel gauge
- Overload protection (kW & kV Ar)
- Low oil pressure protection
- High coolant temperature protection
- Low fuel level protection
- Battery charger alternator failure
- Over-rev protections

Emergency Stop Button

Siren

Terminal block for Automatic Panel connection

RS232 port

Charging Battery

On/off switch

If you are looking for another product then you can consult our catalog other [gruppi elettrogeni terrestri](#).

Images and technical data are not binding. Please always consult the technical data sheet issued by the manufacturer. Manel Service does not assume responsibility for any changes made by the manufacturer.

**Product features:**

Phase: Three phase

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400/230

Engine: SCANIA, DC13 072A 02 14

Emissions Regulations: Not Emitted

Engine rpm (rpm): 1500

Cooling: Water

---



Fuel tank capacity (L): 800  
Running time (h): 11.5 at 75% of the load  
Acoustic pressure: 77 dB(A) at 7 m  
Length (mm): 4810  
Width (mm): 1600  
Height (mm): 2460  
Dry weight (Kg): 5000  
Silenced: Yes  
Super silenced: No  
Voltage regulator: AVR  
Engine manufacturer: Scania  
Continuous power PRP kVA: 500  
Continuous power PRP kW: 400  
Stand-by power LTP kVA: 550  
Stand-by power LTP kW: 440