



Shop name



Generator Set Silenced with Manual Panel 143KVA Stagell

Product price:

16,250.00 € tax excluded

Product description:

Generator Set Silenced with Manual Panel 143KVA Stagell

The 143KVA Stagell Manual Controlled silenced Generator Set is a powerful and reliable solution for your energy needs, designed to operate quietly and efficiently.

This 143KVA Stagell Manual Controlled silenced Generator Set is a three-phase generator set, capable of delivering a maximum power of 114.4 KW (143 KVA). It runs on diesel fuel (Diesel) with a frequency of 60 Hz and a voltage of 400 V.

The heart of the silenced Generator Set with Manual Panel 143KVA Stagell is the FPT NEF N45TM2A engine, a 4-cylinder FPT Iveco with a displacement of 4500 cm³ and a bore x stroke of 104×132 mm. The engine operates at 1800 rpm with a mechanical speed governor and electric starter. The cooling is water-cooled and complies with Stage 2 emissions regulations.

The alternator, a STAMFORD – MECC ALTE – MARELLI MOTORI 4-pole, is equipped with AVR (Automatic Voltage Regulator) for precise voltage regulation.

As for autonomy, the 143KVA Stagell silenced Generator with Manual Panel has a 120L tank and a consumption of 23L/h at 75% load, ensuring approximately 5.2 hours of continuous operation.

One of the main advantages of the 143KVA Stagell silenced Generator with Manual Panel is its silent operation, with a sound pressure of only 1000 psi. 69 dB(A) at 7 meters, making it suitable even in noise-sensitive environments. Its dimensions are 2300 mm (length), 1085 mm (width) and 1670 mm (height), with a weight of 1440 Kg. The degree of protection is IP44.



Technical characteristics:

Phase type: Three-phase

Maximum three-phase power (KW): 114.4

Maximum three-phase power (KVA): 143

Fuel: Diesel

Frequency (Hz): 60

Voltage (V): 400

Engine: FPT NEF N45TM2A

Engine speed (rpm): 1800

Speed ??governor: Mechanical

Starting: Electric

Displacement (cm³): 4500

Number of cylinders: 4

Cooling: Water

Alternator: STAMFORD – MECC ALTE – MARELLI MOTORI

Number of poles: 4

Consumption (L/h): 23lt at 75% of load

Autonomy (h): 5.2

Sound pressure: 69 dB(A) @ 7mt

Length (mm): 2300

Width (mm): 1085

Height (mm): 1670

AVR: Yes



Silenced: Yes

Bore x stroke (mm): 104 x 132 mm

Protection degree: IP44

Weight (Kg): 1440

Tank capacity (L): 120

Product type: Generator set

ATS switch panel: Optional

Voltage regulator: AVR

Engine brand: FPT Iveco

Emissions standard: Stage 2

If you are looking for a similar product then you can consult the entire range of [generator](#) or other types of products in our catalog to find the one that best suits your needs.

Images and technical data are not binding. Please always consult the technical data sheet issued by the manufacturer. Manel Service does not assume responsibility for any changes made by the manufacturer.

Product features:

Phase: Three phase

Maximum power three phase (KW): 114.4

Maximum power three phase (KVA): 143

Fuel: Diesel

Frequency (Hz): 60

Voltage (V): 400

Engine: FPT NEF N45TM2A

Emissions Regulations: Stage 2

Engine rpm (rpm): 1800

Speed governor: Mechanical

Starting system: Elettrico

Engine capacity (cm³): 4500



Number cylinders: 4

Cooling: Water

Alternator: STAMFORD – MECC ALTE – MARELLI MOTORI

Poles: 4

Protection degree: IP44

Bore x stroke (mm): 104 x 132 mm

Tank capacity (L): 120

Consumption (L/h): 23lt at 75% load

Running time (h): 5.2

Acoustic pressure: 69 dB(A) @ 7mt

Length (mm): 2300

Width (mm): 1085

Height (mm): 1670

AVR: Yes

Silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: FPT Iveco

Weight (Kg): 1440