



# LIGHTING TOWER

## 4x320W STAGE V

Product price:

**10,455.00 € tax excluded**

### Product description:

#### STAGE V 4x320W LIGHT TOWER

STAGE V 4x320W LIGHT TOWER is a compact and powerful light tower, designed to provide efficient and reliable lighting. Equipped with a Yanmar 2TNV70 engine running at 1500 rpm, compliant with Stage 5 emissions regulations, this unit runs on diesel and guarantees an exceptional autonomy of 145 hours thanks to an 80-liter tank. It has an electric start and a water cooling system, ensuring stable and long-lasting operation.

The lighting system consists of 4 320W MULTILED lamps that produce a total luminous flux of 255,000 lumens, illuminating an area of 8,800 m<sup>2</sup>. The pole, with a maximum height of 7.6 meters, can be lifted manually and has a 350° rotation to direct the light precisely. The unit is compact both when open (2026x1804x7600 mm) and closed (2026x1140x2390 mm).

With a dry weight of 550 kg, the TORRE FAR 4x320W STAGE V is easily transportable thanks to a slow trailer and an EU-approved road trailer. Its structure is robust, with wind stability up to 100 km/h, and the Linz Electric – Alumen alternator with protection class IP21 and insulation class H guarantees the safety and efficiency of the entire system.

### Technical characteristics:

Fuel: Diesel

Frequency: 50 Hz

Voltage: 230 V

Engine speed: 1500 rpm

Starting: Electric

---



Type of lamps: MULTILED

Lamps: 4 x 320W Multiled

Total lumens: 255,000 Lm

Illuminated area: 8,800 m<sup>2</sup>

Lifting: Manual lifting system

Maximum height: 7.6 m

Open dimensions: 2026x1804x7600 mm

Closed dimensions: 2026x1140x2390 mm

Wind stability: 100 Km/h

Dry weight: 550 kg

Mast rotation: 350°

Transportability: Slow trailer and EU approved road trailer - variable rudder

Engine brand: Yanmar 2TNV70

With/without generator: With generator

Emissions standard: Stage 5

Cooling: Water

Displacement: 570

Tank capacity: 80 L

Autonomy: 145 h

Alternator: Linz Electric – Alumen

Protection class: IP21

Insulation class: H

---



Looking for a product with different features? [HERE](#) you can find the entire range of other specialized brands.

**Product features:**

Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 1500  
Starting system: Elettrico  
Cooling: Water  
Alternator: Linz Electric – Alumen  
Maximum height (m): 7.6  
Tank capacity (L): 80  
Type of lamps: MULTILED  
Lamps: 4 x 320W Multiled  
Illuminated area (m<sup>2</sup>): 8.800  
Total lumens (Lm): 255.000  
Lifting System: Manual lifting system  
Mast rotation: 350°  
Open size (mm): 2026x1804x7600  
Closed size (mm): 2026x1140x2390  
With generator / Without generator: With generator  
Transportability: Slow Trailer and EU homologized road trailer - variable rudder  
Stability to wind (Km/h): 100 Km/h  
Running time (h): 145  
Acoustic pressure: 61 dB (A)  
Dry weight (Kg): 550  
Control unit: InteliNano AMF5 ComAP  
Operating temperature: -25°/ 50° C  
classe di protezione: IP21  
displacement: 570  
Insulation Class: H  
Lifting Hook: Standard  
Fixed Rudder: Standard  
Manual stabilizers: 4+1

