



PRAMAC GSW225V COFANATO CON QUADRO COMANDO AUTOMATICO

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 176

Continuous power three phase (KW): 160.37

Maximum power three phase (KVA): 220

Continuous power three phase (KVA): 200.46

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: VOLVO TAD753GE, turbo intercooled

Speed governor: Electronic

Starting system: Electric

Engine capacity (cm³): 7150

Number cylinders: 6

Cylinders' position: In line

Oil capacity (L): 34

Cooling: Water

Alternator: Mecc Alte ECO38-2SN/4, brushless

Poles: 4

Fuel tank capacity (L): 350

Consumption (L/h): 35.6 at 75% of the load / 44.9 at 100% of the load

Running time (h): 9.8 at 75% of the load / 7.8 at 100% of the load

Acoustic power: 94 dB(A)

Acoustic pressure: 65 dB(A) at 7 m

Length (mm): 3400





Width (mm): 1250

Height (mm): 1980

Dry weight (Kg): 2540

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Volvo

