



Generator set Super-Silenced Manual Control 33KVA Stage3A

Product price:

8,520.00 € tax excluded

Product description:

33KVA Stage3A Super-Silent Manual Control Generator

The Yanmar 4TNV98 33 kVA (26.4 kW) three-phase diesel generator with manual control is the perfect solution for those who need a powerful and reliable power supply in any situation. This super-silent generator, compliant with Stage 3A emissions regulations, combines high performance with extremely quiet operation, ideal for construction sites, events and noise-sensitive environments.

Equipped with a 4-stroke, 4-cylinder, 3319 cm³ diesel engine, operating at 1500 rpm, it guarantees a maximum power of 33 kVA and continuous use of 30 kVA, ensuring continuous and stable power supply. The starter is electric, while the mechanical speed governor allows for simple and precise control of the engine speed.

The generator is equipped with a 4-pole LINZ PRO18S C/4 alternator with AVR voltage regulator, which maintains a constant voltage of 230/400 V and 50 Hz frequency, thus protecting the connected equipment. The integrated manual panel facilitates the management of the generator, making it simple to use even without automatic control systems.

With a 70-liter tank capacity and a consumption of 5.2 liters per hour, the generator offers a runtime of approximately 13 hours, perfect for extended work without the need for frequent refueling. Its compact dimensions (1750x700x1100 mm) and dry weight of 570 kg make it easy to transport and install.

The socket configuration includes a CEE 63A 400V 5-pole and an additional CEE socket, ensuring versatility and safety in electrical connections.

Choose the super-silenced three-phase diesel generator with 33 kVA manual control panel to have power, silence and environmental compliance in a single high-quality product.



Technical characteristics:

Maximum power: 26.4 kW (33 kVA)

Continuous use power: 24 kW (30 kVA)

Fuel: Diesel

Engine: Yanmar 4TNV98, 4-stroke, 4-cylinder, 3319 cm³

Engine speed: 1500 rpm, electric start, mechanical speed governor

Cooling: Water

Alternator: LINZ PRO18S C/4, 4-pole, AVR voltage regulator

Frequency: 50 Hz

Voltage: 230/400 V

Fuel tank capacity: 70 L with consumption 5.2 L/h and autonomy approximately 13 h

Dimensions: 1750 mm (length) x 700 mm (width) x 1100 mm (height)

Dry weight: 570 kg

Noise level: silenced, super silenced

Emissions standard: Stage 3A

Socket configuration: 1 x CEE 63A 400V 5P, 1 x CEE

If you are looking for a product with different features [Click HERE](#). You'll find a product category to suit your needs.

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 26.4

Continuous power three phase (KW): 24



Maximum power three phase (KVA): 33

Continuous power three phase (KVA): 30

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x CEE 63A 400V 5P 1 x CEE 32A 400V 5P 1 x CEE 16A 230V 3P

Engine: Yanmar 4TNV98, 4 stroke

Emissions Regulations: STAGE 3A

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Elettrico

Engine capacity (cm³): 3319

Number cylinders: 4

Cooling: Water

Alternator: LINZ PRO18S C/4

Poles: 4

Fuel tank capacity (L): 70

Consumption (L/h): 5.2

Running time (h): 13 h (Approx.)

Length (mm): 1750

Width (mm): 700

Height (mm): 1100

Silenced: Yes

Super silenced: Yes

Voltage regulator: AVR

