



# PRAMAC LIFTER GX12-35EVO GEL24V-105Ah Electric Stacker

Product price:

**6,330.66 € tax excluded**

## Product description:

### **PRAMAC LIFTER GX12-35EVO GEL24V-105Ah ELECTRIC STACKER**

The PRAMAC LIFTER GX12-35EVO GEL24V-105Ah Electric Stacker is the ideal solution for those looking for a compact, reliable, and high-performance stacker. Designed to operate efficiently in confined spaces, it combines power, stability, and exceptional maneuverability. Thanks to its ergonomic design and advanced technology, this PRAMAC LIFTER electric stacker ensures productivity and safety in any industrial or logistics application.

#### **Main features of the PRAMAC LIFTER GX12-35EVO:**

Rated capacity: 1,200 kg

Lifting height: 3,500 mm

Travel speed: up to 5.2 km/h

Lifting motor: 2.2 kW

Drive motor: 0.7 kW

Operating noise level: only 62 dB(A)

Battery: GEL 24V – 105Ah

Operating weight: 618 kg

The PRAMAC LIFTER GX12-35EVO GEL24V-105Ah Electric Stacker is equipped with an ergonomic technopolymer tiller, featuring proportional lift controls, integrated accelerator, horn, and safety button. The “turtle mode” function allows operation in tight spaces while maintaining full control of the machine.

With a total width of only 800 mm – the same as a Euro pallet – it offers excellent visibility and maneuverability even in narrow aisles.



## Battery and Performance

Equipped with powerful GEL 24V 105Ah batteries, the PRAMAC LIFTER GX12-35EVO GEL24V-105Ah Electric Stacker guarantees long autonomy, short charging times, and total maintenance-free operation. The GEL batteries offer outstanding resistance to deep discharges and a longer lifespan compared to traditional lead-acid models.

The integrated charger with cable and Schuko plug makes the unit completely “plug & play”, simplifying daily use.

## Structure and Safety

The compact reinforced steel frame and ABS cover with document holder compartment ensure robustness and practicality. The easily removable components simplify maintenance, while the electric braking system ensures full control and safety in every operating condition.

The wide mast with height indicator allows the operator to precisely monitor the lifting level up to 3,410 mm, maintaining maximum load stability at all times.

## Advantages

Compact and easy to handle — perfect for warehouses and narrow spaces

Extended autonomy thanks to long-life GEL batteries

Proportional electronic control system for precise lifting

Integrated charger for fast and safe recharging

Low maintenance and maximum operational efficiency

The PRAMAC LIFTER GX12-35EVO GEL24V-105Ah Electric Stacker is the perfect choice for companies that require reliability, power, and practicality in a single machine. With its professional performance and PRAMAC's renowned build quality, it stands out as a top-of-the-range model among compact electric stackers.

Are you looking for a forklift similar to the PRAMAC GX12-35EVO GEL24V-105Ah but with different features? [CLICK HERE](#) to view our full range.

## **Product features:**

Drive: Electric

Operator type: Pedestrian

Load capacity (Kg): 1200

Load centre distance (mm): 600

Load axle to end forks (mm): 780

Wheel base (mm): 1234

Service weight (Kg): 618

Axle load, laden rear (Kg): 1187

Axle load, laden front (Kg): 631

Axle load, unladen front (Kg): 456



---

Axle load, unladen rear (Kg): 162  
Tyres: front wheels: POLY  
Tyres: stabilizers wheels: POLY.C.  
Tyres: rear wheels: POLY.C.  
Diameter steering wheels (mm): 250  
Width steering wheels (mm): 76  
Diameter load rollers (mm): 82  
Width load rollers (mm): 70  
Diameter stabilizers wheels front (mm): 100  
Width stabilizers wheels front (mm): 38  
Quantity rear wheels: 2  
Quantity front wheels: 1 driven + 1  
Tread front (mm): 565  
Tread rear (mm): 410  
Height mast lowered (mm): 2250  
Normal free lifting (mm): 80  
Lift height (mm): 3410  
Height mast extended (mm): 3916  
Height of tiller in drive position max (mm): 1330  
Height of tiller in drive position min (mm): 960  
Overall lenght (mm): 1760  
Lenght to face of forks (mm): 610  
Overall width (mm): 800  
Thickness fork (mm): 70  
Width fork (mm): 150  
Fork carriage width (mm): 650  
Distance between fork arms (mm): 560  
Ground clearance at centre of wheelbase (mm): 20  
Aisle width (mm): 2210  
Turning radius (mm): 1430  
Travel speed laden (Km/h): 4.7  
Travel speed unladen (Km/h): 5.2  
Lifting speed laden (m/s): 0.11  
Lifting speed unladen (m/s): 0.19  
Lowering speed laden (m/s): 0.25  
Lowering speed unladen (m/s): 0.30  
Max gradeability laden (%): 5  
Max gradeability unladen (%): 10  
Service brake: Electric  
Drive motor power (KW): 0.7  
Lift motor power (KW): 2.2  
Battery voltage (V): 24  
Battery capacity min (Ah): 105  
Battery capacity max (Ah): 105  
Battery weight min (Kg): 76

---



Battery weight max (Kg): 80

Energy consumption according to VDI cycle (KWh/h): 0.9

Sound level at driver's ear: 62

Type of lifting: Electric

Battery type: GEL

