



Shop name



# PRAMAC LIFTER GX12-42EVO GEL24V-105Ah Electric Stacker

Product price:

**7,865.63 € tax excluded**

## Product description:

### **PRAMAC LIFTER GX12-42EVO GEL24V-105Ah ELECTRIC STACKER**

The PRAMAC LIFTER GX12-42EVO GEL24V-105Ah Electric Stacker is the ideal solution for those who need a compact, powerful, and reliable stacker to work efficiently in confined spaces. With a total width of only 800 mm, an ergonomic side tiller, and wide masts, it offers excellent maneuverability and optimal visibility during every operation.

The PRAMAC LIFTER GX12-42EVO GEL24V-105Ah Electric Stacker is equipped with 24V 105Ah GEL maintenance-free batteries that ensure long life, a high number of charge cycles, and protection against deep discharges. The integrated charger with Schuko plug and spiral cable allows for convenient and safe charging, making this unit an extremely practical plug & play system.

The compact structure of the PRAMAC LIFTER GX12-42EVO GEL24V-105Ah Electric Stacker allows handling loads up to 1200 kg with a maximum lifting height of 4200 mm. The powerful 2.2 kW lifting motor and 0.7 kW traction motor guarantee excellent performance, while the electric brake system ensures safety and precision during load handling.

### **Main Features – PRAMAC LIFTER GX12-42EVO:**

Drive type: Electric

Control type: Walk-behind

Load capacity: 1200 Kg

Rear wheels: 2

Front wheels: 1 drive + 1

Closed mast height: 2600 mm



Free lift: 80 mm

Lifting height: 4110 mm

Total length: 1760 mm

Total width: 800 mm

Fork width: 150 mm

Fork length: 1150 mm

Width between forks: 560 mm

Storage aisle width: 2210 mm

Turning radius: 1430 mm

Travel speed with load: 4.7 Km/h

Travel speed without load: 5.2 Km/h

Traction motor power: 0.7 kW

Ergonomic technopolymer tiller with proportional controls, horn, hour counter display, and battery status indicator.

“Turtle mode” function for precise movements in tight spaces, even with the tiller in a vertical position.

ABS cover with document compartment, easily removable to simplify maintenance.

Mast with height indicator for perfect visibility and total control during fork lifting.

Thanks to its robust and compact design, the PRAMAC LIFTER GX12-42EVO GEL24V-105Ah Electric Stacker is perfectly suited for warehouses, logistics centers, and production areas where efficiency, safety, and reliability are essential. With a noise level of only 62 dBA and low energy consumption (0.9 kWh/h), it is an efficient, quiet, and sustainable machine.

Are you looking for a forklift similar to the PRAMAC LIFTER GX12-42EVO GEL24V-105Ah but with different features? [CLICK HERE](#) to explore our full range.

#### **Product features:**

Drive: Electric

Operator type: Pedestrian

Load capacity (Kg): 1200

Load centre distance (mm): 600

Load axle to end forks (mm): 780

Wheel base (mm): 1234

Service weight (Kg): 644

Axle load, laden rear (Kg): 1173

Axle load, laden front (Kg): 671

Axle load, unladen front (Kg): 471

Axle load, unladen rear (Kg): 173

Tyres: front wheels: POLY

Tyres: stabilizers wheels: POLY.C.

---



Tyres: rear wheels: POLY.C.  
Diameter steering wheels (mm): 250  
Width steering wheels (mm): 76  
Diameter load rollers (mm): 82  
Width load rollers (mm): 70  
Diameter stabilizers wheels front (mm): 100  
Width stabilizers wheels front (mm): 38  
Quantity rear wheels: 2  
Quantity front wheels: 1 driven + 1  
Tread front (mm): 565  
Tread rear (mm): 410  
Height mast lowered (mm): 2600  
Normal free lifting (mm): 80  
Lift height (mm): 4110  
Height mast extended (mm): 4616  
Height of tiller in drive position max (mm): 1330  
Height of tiller in drive position min (mm): 960  
Height lowered (mm): 90  
Overall length (mm): 1760  
Length to face of forks (mm): 609  
Overall width (mm): 800  
Thickness fork (mm): 70  
Width fork (mm): 150  
Length fork (mm): 1150  
Fork carriage width (mm): 650  
Distance between fork arms (mm): 560  
Ground clearance at centre of wheelbase (mm): 20  
Aisle width (mm): 2210  
Turning radius (mm): 1430  
Travel speed laden (Km/h): 4.7  
Travel speed unladen (Km/h): 5.2  
Lifting speed laden (m/s): 0.11  
Lifting speed unladen (m/s): 0.19  
Lowering speed laden (m/s): 0.25  
Lowering speed unladen (m/s): 0.30  
Max gradeability laden (%): 5  
Max gradeability unladen (%): 10  
Service brake: Electric  
Drive motor power (KW): 0.7  
Lift motor power (KW): 2.2  
Battery voltage (V): 24  
Battery capacity min (Ah): 105  
Battery capacity max (Ah): 105  
Battery weight min (Kg): 78  
Battery weight max (Kg): 78

---



Shop name

---

Energy consumption according to VDI cycle (KWh/h): 0.9  
Sound level at driver's ear: 62  
Type of lifting: Electric  
Battery type: GEL



---

PrestaShop