



PRAMAC GSW280V COFANATO CON QUADRO COMANDO AUTOMATICO

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 220

Continuous power three phase (KW): 202.68

Maximum power three phase (KVA): 275

Continuous power three phase (KVA): 253.35

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: VOLVO TAD754GE, turbo intercooled

Speed governor: Electronic

Starting system: Electric

Engine capacity (cm³): 7150

Number cylinders: 6

Cylinders' position: In line

Oil capacity (L): 20

Cooling: Water

Alternator: Mecc Alte ECO38-1LN/4, brushless

Poles: 4

Fuel tank capacity (L): 636

Consumption (L/h): 46.4 at 75% of the load / 57 at 100% of the load

Running time (h): 13.7 at 75% of the load / 11.3 at 100% of the load

Acoustic power: 97 dB(A)

Acoustic pressure: 68 dB(A) at 7 m

Length (mm): 3951



Shop name

Width (mm): 1438

Height (mm): 2085

Dry weight (Kg): 2990

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Volvo



PrestaShop