



GENERATOR PTO SINGLE/THREE PHASE 24,2 KVA AVR

Product price:

2,290.00 € tax excluded

Product description:

GENERATOR PTO SINGLE/THREE PHASE 24,2 KVA AVR

Generator PTO Single-phase/three-phase with 3000 rpm tractor attachment, capable of delivering 24,2KVA power, complete with **AVR voltage regulator.**

Easy to transport, install and position due to its compact size, this model is ideal for mounting on a tractor unit. The gimbal-mounted generator has a tractor power requirement of 45 HP and a PTO speed of 435 rpm.

These compact, rugged and easy-to-use generator sets come complete with a 3-point hitch base for secure attachment to any tractor.

Power transmission is via the universal joint (not included), which is connected to the generator set multiplier.

Tractor attachment generators are designed primarily for farms, ranches, ranches and mountain pastures but are easily adapted to any emergency situation.

Professional tractor unit making it one of the best choices compared to its competitors, equipped with a sturdy structure with protective frame.

Technical characteristics:

Phase type: Single-phase / Three-phase

Continuous power: 22 KVA Continuous power: 17.6 KW Emergency power: 24.2 KVA Emergency power: 19.4 KW



Voltage: 230/400 V Frequency: 50 Hz

Engine speed: 3000 rpm

Necessary tractor power: 45 hp

PTO speed: 435 rpm Multiplier ratio: 1: 6.9

Multiplier oil capacity: 0.7 Lt

Alternator: NSM, self-excited, with brushes

Voltage regulator: AVR

Length: 958 mm Width: 843 mm Height: 1003 mm Weight: 150 Kg

Are you looking for a product with different technical characteristics? <u>HERE</u> you can find the entire range of shaft-driven generator sets from specialized brands.

Non-binding images and technical data.

Product features:

Phase: Single phase / Three phase

Frequency (Hz): 50 Voltage (V): 230 / 400 Engine rpm (rpm): 3000 Oil capacity (L): 0.7 Alternator: With brushes

Poles: 2

Protection degree: IP23 PTO speed (round/min): 435 Required tractor power: 45 HP Transmission ratio: 1:6.9

Length (mm): 958 Width (mm): 843 Height (mm): 1003

Silenced: No

Super silenced: No Voltage regulator: AVR

