



PRAMAC GSW10Y COFANATO CON QUADRO COMANDO MANUALE (MCP)

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 26

Continuous power three phase (KW): 24.4

Maximum power three phase (KVA): 32.5

Continuous power three phase (KVA): 30.5

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 63A 3P+N+T

Engine: Yanmar 4TNV98-IGPGE, naturally aspirated

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 3319

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 10.5

Cooling: Water

Alternator: Mecc Alte ECP28-VL/4, brushless

Poles: 4

Fuel tank capacity (L): 68

Consumption (L/h): 5.8 at 75% of the load / 7.7 at 100% of the load

Running time (h): 11.7 at 75% of the load / 8.8 at 100% of the load

Acoustic power: 95 dB(A)

Acoustic pressure: 66 dB(A) at 7 m



Length (mm): 2000

Width (mm): 920

Height (mm): 1310

Dry weight (Kg): 773

Inverter: No

AVR: Yes

Compound: No

Silenced: Yes

Super silenced: Yes

