



# Generator Set Silenced Non-Emission 250KVA



**Product price:**

**32,250.00 € tax excluded**

## **Product description:**

### **Silent, Non-Emitting Generator Set 250KVA**

This generator delivers a maximum three-phase power of 200 kW (250 kVA) and a continuous power of 180 kW (225 kVA).

It operates at a frequency of 50 Hz and provides a standard voltage of 230 / 400 V, suitable for most industrial and commercial applications.

Voltage stability is ensured by an AVR voltage regulator, which protects sensitive connected electronic equipment.

The generator is equipped with a Perkins 1206A-E70TTAG2 engine, a 6-cylinder in-line diesel unit with a displacement of 7035 cm<sup>3</sup> and water cooling.

The engine operates at 1500 rpm, a feature that ensures greater durability and lower noise during use. extended.

The alternator is a Mecc Alte ECO38-3S/4 synchronous model, known for its reliability. The starter is electric and the engine speed is managed electronically for greater precision.

## **Technical Features:**

Maximum three-phase power: 250 KVA

Maximum three-phase power: 200 KW

Fuel: Diesel

Voltage: 230/400 V

Engine: Perkins 1206A-E70TTAG2

Starter: Electric

Length: 3300 mm

Width: 1100 mm

Height: 1770 mm

Weight: 2450 kg

---



If you are looking for a similar product but with different characteristics [CLICK HERE.](#)

**Product features:**

Phase: Three phase

Maximum power three phase (KW): 200

Continuous power three phase (KW): 180

Maximum power three phase (KVA): 250

Continuous power three phase (KVA): 225

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: Perkins 1206A-E70TTAG2

Engine rpm (rpm): 1500

Speed governor: Electronic

Starting system: Elettrico

Engine capacity (cm<sup>3</sup>): 7010

Number cylinders: 6

Cylinders' position: In line

Cooling: Water

Alternator: LEROY SOMER

Poles: 4

Protection degree: IP23

Fuel tank capacity (L): 170

Consumption (L/h): 35.7 Lt/h al 75% del carico

Acoustic pressure: 70 dB(A)

Width (mm): 1100

Height (mm): 1770

Dry weight (Kg): 2450

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR

