



DazeBox T Urban Electric Vehicle Charging Station 64A 2x22.2KW, with MID meter

Product description:

DazeBox T Urban Electric Vehicle Charging Station 64A 2x22.2KW

Unmatched durability and toughness for public charging. Urban integrates all of Daze's advanced charging technology into a sleek, ultra-compact stainless steel body, engineered for maximum toughness and resilience.

Durability and easy maintenance

Urban is IK10 certified, designed to withstand harsh environments with its rugged AISI 304 stainless steel body. The large front door provides easy access to internal components, enabling quick and efficient maintenance.

Effortless installation

Designed for maximum simplicity, the Duo requires only a single supply line and eliminates the need for trip coils, with integrated RCBOs already built in. For added peace of mind, optional protection against permanent and transient overvoltages is available.

Balancing between two charging points

Powered by a single supply line, Duo intelligently and automatically allocates available energy between both charging points. This ensures optimal charging performance for multiple vehicles without the need for additional infrastructure.

Product features:



Phase: Three phase

Nominal current (A): 64

Charging socket: mode 3

IP Protection: IP54

Operating temperature: Da -30° C / +55°

Dimensions [mm]: 1360 x 245 x 180 mm

Maximum power consumption: 2x22,2 kW

Connection points: 2x25

Protezione IK: IK10

Lunghezza cavo: 5 m

Protezione magnetotermica differenziale: Tipo A (30 mA), curva C

Protezione contro le sovratensioni: SPD Tipo 2 40kA / POP 285 V $\pm 5\%$

Misuracorrente certificata MID: Sì