



# PRAMAC GSW10Y COFANATO CON QUADRO COMANDO MANUALE (MCP)

## Product description:

### Product features:

Phase: Three phase

Maximum power three phase (KW): 436.8

Continuous power three phase (KW): 403.77

Maximum power three phase (KVA): 546

Continuous power three phase (KVA): 504.71

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: VOLVO TAD1641GE, turbo intercooled

Emissions Regulations: Stage 2

Speed governor: Electronic

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 16120

Number cylinders: 6

Cylinders' position: In line

Oil capacity (L): 48

Cooling: Water

Alternator: Mecc Alte ECO40-3S/4, brushless

Poles: 4

Fuel tank capacity (L): 636

Consumption (L/h): 77.6 at 75% of the load / 104.4 at 100% of the load

Running time (h): 8.2 at 75% of the load / 6.1 at 100% of the load

Length (mm): 3500

Width (mm): 1500





---

Height (mm): 2120  
Dry weight (Kg): 3467  
Silenced: No  
Super silenced: No  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Volvo