



PRAMAC GSW65I CANOPIED WITH MANUAL CONTROL PANEL

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 53.14

Continuous power three phase (KW): 48.18

Maximum power three phase (KVA): 66.43

Continuous power three phase (KVA): 60.22

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: FPT NEF45SM1A, turbo intercooled

Emissions Regulations: Stage 2

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 4500

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 12.8

Cooling: Water

Alternator: Mecc Alte ECO/P32-2L/4, brushless

Poles: 4

Fuel tank capacity (L): 209

Consumption (L/h): 10.2 at 75% of the load / 13.7 at 100% of the load

Running time (h): 20.4 at 75% of the load / 15.3 at 100% of the load

Acoustic power: 95 dB(A)

Acoustic pressure: 67 dB(A) at 7 m

Length (mm): 2400

Width (mm): 1000



Height (mm): 1530

Dry weight (Kg): 1440

Silenced: Yes

Super silenced: Yes

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: FPT Iveco

