



PRAMAC GSW65I CANOPIED WITH MANUAL CONTROL PANEL

Product price:

15,108.57 € tax excluded

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 53.14 Continuous power three phase (KW): 48.18 Maximum power three phase (KVA): 66.43 Continuous power three phase (KVA): 60.22

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 400

Engine: FPT NEF45SM1A, turbo intercooled

Emissions Regulations: Stage 2 Speed governor: Mechanical Starting system: Electric Engine capacity (cm³): 4500

Number cylinders: 4 Cylinders' position: In line Oil capacity (L): 12.8

Cooling: Water

Alternator: Mecc Alte ECO/P32-2L/4, brushless

Poles: 4

Fuel tank capacity (L): 209

Consumption (L/h): 10.2 at 75% of the load / 13.7 at 100% of the load Running time (h): 20.4 at 75% of the load / 15.3 at 100% of the load

Acoustic power: 95 dB(A)

Acoustic pressure: 67 dB(A) at 7 m

Length (mm): 2400



Width (mm): 1000 Height (mm): 1530 Dry weight (Kg): 1440

Silenced: Yes

Super silenced: Yes ATS Switch device : No Voltage regulator: AVR

Engine manufacturer: FPT Iveco

